



Multiple remote sensing assessment of the catastrophic collapse in Langtang Valley induced by the 2015 Gorkha Earthquake

Hiroto Nagai¹, Manabu Watanabe², Naoya Tomii³, Takeo Tadono¹, Shinichi Suzuki¹

¹Earth Observation Research Center, Japan Aerospace Exploration Agency, 2-1-1 Sengen, Tsukuba, Ibaraki, 305-8505, Japan

²School of Science and Engineering, Tokyo Denki University, Ishizaka, Hatoyama-machi, Hiki-gun, Saitama, 305-0394, Japan

³Satellite Applications and Operations Center, Japan Aerospace Exploration Agency, 2-1-1 Sengen, Tsukuba, Ibaraki, 305-8505, Japan

Correspondence to: Hiroto Nagai (nagai.hiroto@jaxa.jp)

Abstract. We demonstrated an assessment of the sediments caused by a catastrophic avalanche, induced by the main shock of the 2015 Gorkha Earthquake in Nepal. Calculation of decreasing coherence and visual interpretation of amplitude images by means of the Phased Array-type L-band Synthetic Aperture Radar-2 (PALSAR-2) have a high potential for delineating the hazardous zone. These delineated outlines area highly consistent with that from a high-resolution optical image of WorldView-3 (WV-3). The delineated sediment collapse areas were estimated as 0.63 km² (PALSAR-2 coherence calculation), 0.73 km² (PALSAR-2 visual interpretation), and 1.09 km² (WV-3), respectively. In the WV-3 image, surface features were classified into 15 segments, with the flowing, scattering, and other characteristics implying different physical properties; the different features suggest sequential collapse from multiple sources. By means of satellite-derived pre- and post-event digital surface models, differences in the surface altitudes of the collapse events estimated the total volume of the sediments as 6229.1 × 10³ m³, with an error possibility between 5363.3 × 10³ to 7314.8 × 10³ m³, most of which are distributed along the river bed and the water stream. Further altitude measurements after ice/snow melting would reveal a contained volume of melting ice and snow, which will contribute to numerical avalanche simulation and source considerations.

Keywords. ALOS-2, InSAR, WorldView-3, ALOS World 3D, avalanche, Nepal, Himalaya

1 Introduction

A great earthquake of 7.8 Mw, namely the 2015 Gorkha Earthquake, occurred in the district of Lamjung, central Nepal on April 25, 2015 (Ge et al. 2015; Parameswara et al. 2015), which caused more than 9,000 deaths and 23,000 people to be injured (e.g., Roy et al. 2015). Damages in urban areas were especially caused on stone/brick masonry structures (Goda et al. 2015), whereas numerous landslides were induced in rural/mountain areas (ICIMOD 2015a; Kargel et al. 2015).

The most catastrophic collapse in the mountainside was reported in the Langtang valley, located 70 km north of Kathmandu (ICIMOD 2015b; Kargel et al. 2015). Landslides, avalanches, and sudden air pressure wave traveled from a south-facing



steep slope to the bottom of a U-shaped valley. The fallen materials, i.e., a mass of boulders, snow, and ice, covered the valley bottom involving almost all of the buildings in Langtang Village. At the opposite side of the valley, trees were prostrated and lost their leaves by the sudden air pressure wave. More than 170 villagers (reaching its double including trekkers and porters) were killed (or left missed) in this event.

- 5 The Langtang Valley is one of the most popular trekking routes in the Nepal Himalaya. Rapid risk assessment and reconstruction of the local community are required for the surviving villagers. Geospatial information obtained by satellite observations should be used to perform reasonable in-situ survey in such a remote mountainous region. Furthermore, the scientific understanding of this huge collapse is definitely important for the consideration of how to avoid similar catastrophic events in the future. In this study, we demonstrate (1) the identification with synthetic aperture radar (SAR) for
- 10 urgent response, (2) the mapping and interpretation of physical property with high-resolution optical imagery, and (3) the volume estimation using the difference between pre- and post-event digital surface models (DSMs). These results are then compared to evaluate effectiveness of SAR analysis for hazard response and to discuss initial situation of this collapse.

2 Data set and Processing

2.1 Study site

- 15 The catastrophic collapse was caused in the middle of Langtang Valley (28°12'50"N, 85°30'5"E), one of the national parks in Nepal. The main river in this valley, the Langtang Khola, flows from the east to the west, and joins the main stream, Bote Kosi (Trisuli Gandaki), at the end of the valley near a village, Syabru Bensi (Ono and Sadakane 1986). The length of the valley is approximately 50 km, and the width ranges from 1 to 2 km. The Langtang Valley is a famous trekking course for the tourists, and it has been called "one of the most beautiful valleys in the world." A typical U-shaped valley formed by
- 20 glaciation. The Lirung, Khyimjung, Yala, Shalbachum, Langtang, and Langshisa glaciers are located 4100 m above sea level (a.s.l.). In addition, several unnamed glaciers are distributed along both the ridges of the U-shaped valley (Shiraiwa and Watanabe 1991), where Mt. Langtang Lirung is the highest peak. The village of Langtang was called "Yul" by the villagers (Ono and Sadakane 1986). The main local occupations are farming and tourism. Many temporary houses called "Kalkha" were built around the village for livestock farming, i.e., for the transhumance of yaks.

25 2.2 Synthetic aperture radar imagery

- In order to estimate the damages after the earthquake on April 25, the Japan Aerospace Exploration Agency carried out an emergency observation with the Phased Array type L-band Synthetic Aperture Radar-2 (PALSAR-2) onboard the Advanced Land Observing Satellite-2 (ALOS-2, "DAICHI-2") aiming central Nepal at 7:02 on April 26 (GMT). This image was taken on the left-looking strip-map mode with a 3-m spatial resolution along the descending orbit of Path 55. Visual interpretation
- 30 of the orthorectified backscatter amplitude image of HH polarization (product level 2.1) was performed. A pre-event PALSAR-2 image taken at 6:13 on December 28, 2014 was used for comparison. This image was taken in a right-looking



strip-map mode with a 3-m spatial resolution along the descending orbit of Path 48. Visual interpretation of the orthorectified backscatter amplitude image of HH polarization (product level 2.1) was simultaneously performed.

Not only the amplitude imagery, but also the phase information emitted and received by the synthetic aperture radar (SAR) contributes to the situational awareness. Coherence calculation quantifies the similarity between the pre-event and post-event
5 images. Decreasing coherence suggests changes in surface features. This was utilized to detect the destruction in urban areas induced by the 1995 Hyogoken-nanbu Earthquake (Yonezawa and Takeuchi 2001) and by the 2011 East Japan earthquake (Tamura and El-Gharbawi 2015), as well as the damages caused by the liquefaction of a coastal area (Kobayashi et al. 2011). This method is applied to detect mountain surface changes using the PALSAR-2 data. Slight coherence changes can be caused regularly such as rockfall, vegetation growth, avalanche, and other natural phenomena in the mountainous area. This
10 is called temporal decorrelation, and depends on the land surface type. To take into account the temporal decorrelation and to emphasize the earthquake-induced coherence, normalized coherence decrease (NCD) is defined as

$$\gamma_{diff} = \frac{\gamma_{pre} - \gamma_{int}}{\gamma_{pre} + \gamma_{int}} \quad (1)$$

where γ_{pre} is the coherence value between two images before the earthquake (October 4, 2014, and February 21, 2015) and
 γ_{int} is the coherence value between those over the earthquake (February 21 and May 2, 2015). These data were acquired
15 from a same orbit with a spatial resolution of 10 m.

Secondly, numerous noises are removed by focal statistics. In the NCD raw image, all pixel values are overwritten by the mean values within 15-pixel circles around each pixel. This filter emphasizes the concentration of high values, whereas the homogeneously scattered high values are de-emphasized.

2.3 Pre-event optical imagery and DSM

20 Pre-event optical satellite imagery and its three-dimensional view were generated to grasp the previous situation in further details. Images of the Panchromatic Remote-sensing Instrument for Stereo Mapping (PRISM) and the Advanced Visible and Near Infrared Radiometer type 2 (AVNIR-2) onboard the Advanced Land Observing Satellite (ALOS) were acquired at 5:02 on October 12, 2008, which were combined into a orthorectified pan-sharpened image. It is a visible color image with a spatial resolution of 2.5 m. A DSM dataset “ALOS World 3D (AW3D)” was used for this study. AW3D was generated from
25 numerous (>3 million scenes) PRISM nadir, forward, and backward images, which were taken through ALOS operation period (2006 to 2011), automatically stacked, and synthesized into a global DSM dataset with a horizontal spacing of 5 m (Tadono et al., 2015). In addition to its finer resolution than existing datasets such of the Shuttle Radar Topography Mission (SRTM) and the Global Digital Elevation Model by Advanced Spaceborne Thermal Emission and Reflection Radiometer (ASTER GDEM) (larger than 30 m), occasional anomaly values was excluded in the generation process as well as
30 occasional cloud cover filled with other scenes. As a result, an accuracy of 4.10 m root mean square for the vertical component versus globally distributed ground control points (4622 points) was reported (Tadono et al., 2015). The



orthorectified pan-sharpened image was overlain on the AW3D DSM with a pixel spacing of 5 m to show a three-dimensional view for interpretation.

2.4 Post-event optical imagery and DSM

Post-event optical satellite imagery and DSM were used to recognize the damaged situation in detail. A DigitalGlobe's satellite, WorldView-3 (WV-3) observed the Langtang valley on May 8, 2015, with a panchromatic sensor of 0.31 m spatial resolution and a multispectral sensor of 1.24 m spatial resolution to generate a set of pan-sharpened stereo pair imagery. Using these data, a post-event DSM in a pixel spacing of 2 m was produced by NTT DATA as its commercial service. In two sites neighboring to the sediment surface, relative calibration/validation of this DSM and the AW3D DSM was performed and summarized in a supplementary material. A pan-sharpened image (high-resolution and composite-color image) generated from one scene of the pair was orthorectified by an author with 178 tie points onto the PRISM image taken on October 12, 2008.

3 Results

3.1 SAR amplitude imagery

A post-event PALSAR-2 backscatter amplitude image is shown in Fig. 1a, and a pre-event image is shown in Fig. 1b. The brightness of these images corresponds to the amplitude of microwave signal reflected to the PALSAR-2 antenna. The difference between the two represents a completely modified surface feature. The mass of the sediment is identifiable only in the post-event image within an area of 0.73 km² (centroid: 28°12'54"N, 85°30'14"E), ranging approximately 1500 m from the upstream to the downstream of the Langtang Khola and 700 m from the upper to the bottom part of the U-shaped valley. Comparing the pre-event PALSAR-2 backscatter amplitude image (Fig. 1b) and an ALOS PRISM/AVNIR-2 pan-sharpened image taken on October 12, 2008 (Fig. 1c), bright points and a valley-shaped feature correspond to buildings and water streams, respectively. These features completely disappear in Fig. 1a, which means that they have been filled by the sediment mass after the quake. A three-dimensional view of the ALOS PRISM/AVNIR-2 image overlaid on the AW3D DSM is shown in Fig. 1d. This sediment area is located below the terminus of a glacier on the north-facing slope. Another glacier flows toward the debris-covered area of the former glacier. This geography suggests a possibility that a large volume of materials travelled from these glaciers with an extremely high potential energy.

3.2 SAR coherence decrease

NCD is calculated from the PALSAR-2 images (Fig. 2a). NCD values greater than 0.2 are reclassified into multiple colors with 0.05 steps, in which scattered NCD dots are difficult to be identified (Fig. 2a). After a focal statistics process with the 15-pixel circle, noisy pixels were moderated and several parts with a high NCD appeared (Fig. 2b). One of the high-value areas (>0.2) correspond to the sediment outline delineated from the PALSAR-2 amplitude image (p in Fig. 2b). Separated



from a connecting upper outline at the narrowest part (< 5 -pixel width), this part has an area of 0.63 km^2 with a centroid of $[28^\circ 12' 57'' \text{N}; 85^\circ 30' 14'' \text{E}]$. Visual interpretation of the amplitude images (Fig. 1) and NCD calculation (Fig. 2) yield a similar result for the collapsed sediments (Fig. 2). Moreover, the both methods are not hindered by the cloudy weather, and hence, have a great potential to immediately indicate a catastrophic collapse and contribute to decision-making for such hazards in the monsoon season.

Furthermore, above the sediment mass, two parts on the south-facing slope show high-NCD concentrations in (q) 0.22 km^2 and (r) 0.07 km^2 areas (Fig. 2b). They are located at the downstream periphery of the Glacier Termini, suggesting the consequent collapse from the tributary glacier to the main glacier. High NCD does not appear on the glacier surfaces possibly because frequent avalanches and glacier flows cause regular changes in the surface. For such surfaces, the changes uniquely caused by an earthquake could be identified by NCD calculation.

3.3 Collapse mapping with a post-event optical imagery

Identification and mapping of the surface features were performed by interpreting the high-resolution satellite imagery (Fig. 3a). In total, 1.09 km^2 sediment cover is delineated including apertures (no-sediment patches), whereas three inclusive parts have little sediment exposure (Ap. 1 to 3). The surface features were classified into 15 segments (Seg. 1 to 15) by interpreting the sediment darkness, flow, scatter, and other surface characteristics (Fig. 3a; Table 1).

According to the sediment darkness interpreted with the WV-3 image, segments were classified into “dark” (Seg. 1 to 4), “light” (Seg. 5 and 6), “medium” (Seg. 7 to 11), and “dark” (Seg. 12 to 15) groups (Table 1). Further, Segs. 1 and 2 have relatively large area of apertures between sediment-covered surfaces, which implies that the materials have scattered directly from the mountainside without flowing. Similar darkness is seen in Segs. 3 and 4, with the former having some areas of apertures (scattering) and the latter consistently flowing downstream in a narrow path connecting to Seg. 5 without aperture. Segment 5 has a consistent flow to the downstream, filling the path of the water stream (see Fig. 1c) with identifiable boulders, whereas Seg. 6 has bright streaks along its flow rather than boulders. Segments 7 to 11 have similar medium darkness, in which Seg. 7 has a flowing feature and Seg. 9 has an additional mud-like feature filling the riverbed in the upstream of Seg. 5. Segments 10 and 11 are located at the opposite side of the U-shaped valley beyond the river (i.e., on a north-facing slope), with Seg. 11 having a much scattered (splashed) distribution. Moreover, prostrated trees are identifiable in Seg. 11. Segments 12 to 15 have darker sediments as compared to Segs. 7-11. Additionally, Segs. 13 and 15 have large apertures, and Seg. 14 is detached from the main sediment mass.

Classifying the sediment surfaces into several segments suggests that this collapse contains various kinds of sediment sources. Multiple layers of sediments with different origin, volume, viscosity, and other surface features do not suggest a single (instant) collapse episode, but imply a continuous sequence of falling from multiple sources in a short period of time.



3.4 Surface altitude changes

According to the relative calibration/validation of the AW3D and WV-3 DSMs (see the Supplementary material), An horizontal offset of 5 m (1 pixel) to the west and an altitude offset of +27.0 m were added to the AW3D DSM to meet the WV-3 DSM with the best consistency. Possible altitude error of 1.5 m was given to calculate minimum and maximum
5 volumes. After the calibration and validation, the difference between the post-event WV-3 DSM and the pre-event AW3D DSM revealed an increase in surface altitude in the collapse site reaching a maximum of 46.7 m (Fig. 3b; Table 1). The increase in the altitude was especially pronounced in Segs. 5 and 9 along the river bed (Fig. 3), which was likely caused by sediment deposition. In these segments, the mean increase in altitude are 20.3 m and 22.0 m, respectively; whereas mean values smaller than 3 m or those no greater than 11 m were measured on other segments. Considering the potential DSM
10 accuracy (see the Supplementary material), changes in a scale of 1.5 m have a greater dominance of uncertainty. We note that the negative values are replaced by 0 to avoid any unnatural errors.

Calculating the altitude change and surface area, a total volume of $6229.1 \times 10^3 \text{ m}^3$ was estimated without error consideration. Most of the volume belongs to Seg. 5 ($3612.6 \times 10^3 \text{ m}^3$; 58.0%) followed by Seg. 9 ($1036.5 \times 10^3 \text{ m}^3$; 16.7%). In order to figure out the possible range of volume estimation uncertainty, we assumed 1.5 m as the error range for altitude
15 measurements. When the altitude change in every segment is homogeneously underestimated to be 1.5 m and the negative values are replaced by 0, the total volume is then estimated to be $5363.3 \times 10^3 \text{ m}^3$ (Table 1). When the altitude change in all areas is homogeneously overestimated to be 1.5 m, the total volume is estimated to be $7314.8 \times 10^3 \text{ m}^3$. In these estimations, +1.5 m offset is also given to the aperture patches because they were difficult to be excluded manually. The real sediment volume is thus estimated to be around $6229.1 \times 10^3 \text{ m}^3$, no smaller or greater than that range.

20 4 Discussion

4.1 SAR-derived surface changes

The sediment outline delineated from the PALSAR-2 amplitude image has an area of 0.73 km^2 , which is very close (i.e. contained area difference smaller than 5%) to what Kargel et al. (2015) measured with DigitalGlobe's high-resolution optical satellite images (0.751 to 0.761 km^2). Hazard scale is thus able to be known similarly by the both methods. The outline
25 delineated from the PALSAR-2 image reaches 67.0% of the area obtained from the WV-3 image with detail visual interpretation including scattered materials (1.09 km^2) (Fig. 4). Its spatial coverage corresponds to Segs. 5, 6, 7, 8, 9, 12, 13, and parts of Segs. 4 and 14. Most of the flowing segments are included in that coverage, whereas most of the scattered segments are excluded (Fig. 4; Table 1). It suggests that scattered materials are difficult to be recognized with a 3-m spatial resolution of PALSAR-2 imagery. Furthermore, sediments on the north-facing slopes are also ignored. Possibly, the
30 microwave reflection from/to PALSAR-2 was hindered by the very steep mountain hillslope.



The sediment outline extracted by NCD calculation has an area of 0.63 km², which is 58.0% of that from the WV-3 image. Its spatial coverage corresponds to Segs. 6, 7, 8, 12, 13, 14, and parts of Ap. 1, Seg. 3, and Seg. 5, whereas Segs. 9, 10, 11, and 15 are missed. NCD indication on the little coverage of sediments on Ap. 1 can be explained if the surface materials before the avalanche were extensively blown away (e.g., from vegetation to bare terrain). No NCD indication along the riverbed is explainable by the geomorphic alternation constitutively caused by the river erosion, which de-emphasizes the avalanche-caused change in the NCD index. North-facing slopes were covered by forestry, where little NCD is explainable owing to growing trees and seasonal defoliation. Two extra parts of high NCD value caused on the valley bottom (i.e. villages of Chyamki and Singdum) ((s) in Fig. 2b) are corresponding to other collapse occurrences which were identifiable with an optical image shown in Fig. S6c of Kargel et al. (2015).

5

10 The geospatial information derived from PALSAR-2 is, thus, usable for disaster response, although the microwave characteristics should be carefully considered. Without pre-event archived data from the same orbit, interferometric SAR technique cannot be used. Instead, a post-event backscatter amplitude image is to be interpreted visually with assistance of other satellite images. The visual interpretation needs careful examination by changing the brightness and contrast of the image, because microwave reflection is influenced simultaneously by both the physical properties and the geomorphic shape of the target area. Through this observation, we have recognized that the visual identification of an unknown hazard only using images is difficult. Therefore, we needed some information about the place and the type of hazard being investigated before interpretation so far. Nevertheless, the approximate scale of the collapse was successfully recognized and provided to the related authorities for emergency response.

15

Accumulation of the archived data more than once from each orbit enables the coherence normalization to emphasize the unusual coherence decrease by a hazard. Furthermore, removing the small patches by means of focal statistics successfully resulted in sediment extraction, which is highly consistent with that from an optical satellite image. For other kind and scale of hazards, the parameter settings (i.e., circle size to obtain a mean value) needs to be assessed and validated through several case studies. We have confirmed that the NCD calculation cannot be used for slightly, but constitutively changing terrains, such as river beach and vegetation.

20

25 In terms of the avalanche source, we found two parts of high NCD values above the collapse sediment on the hillslope ((q) and (r) in Fig. 2b). On the glacier surfaces, regular flowing could de-emphasize the unusual change caused by the avalanche or other collapse events, even if they had happened. The two parts suggest that the falling materials went through these parts and altered their surface features. We could not detect the drastic surface changes in the uphill between AW3D (pre-event) and WV-3 (post-event) images, but Lacroix (2016) supported our suggestion by comparison of DSMs generated from Satellite Pour l'Observation de la Terre (SPOT). Such an extremely-steep slope is difficult to obtain an accurate DSM from most of satellite images, therefore NCD would be preferable focus to be coupled with DSM comparison.

30



4.2 Spatial distribution of sediment volume and details

Multiple segments of the collapsed sediment classified with a WV-3 image imply different sediment sources that have fallen continuously in a short period of time, generating sediment layers (Fig. 3). We could not interpret their layer sequence in detail, but found the different physical properties, i.e., directly fallen and scattered within those places and/or once fallen and flowing the downstream. Especially, Segs. 10 and 11 are located at the end of the flowing parts (Seg. 7 to 9) and splashed onto the opposite hillslope, which implies extremely high potential energy from the source to leap for this range (> 500 m). Splashing direction of Seg. 11 is consistent with the direction of the prostrated trees, which implies that the extreme air pressure happened at the same time of this splashing.

Thick layers of sediments are interpreted in Segs. 5 and 9 as well as the river-side parts of Segs. 4 and 10. A large volume of the muddy sediments in Seg. 9 is likely to have traveled through Seg. 7, by which the local buildings (Fig.1c) were destroyed and swept away. On the other hand, the pre- and post-avalanche DSM difference estimated the thinner sediment layers (within an uncertain small scale for the DSM accuracy) in Segs. 6, 7, and 12, regardless of their complete coverage without the aperture. Thin layers (< 5 m) remain after the avalanche with little dominance of volume.

Kargel et al. (2015) estimated total mass of this sediment as $\sim 3.3 \times 10^9$ kg, assuming homogeneous thickness of 2 m on its entire surface. Our study revealed heterogeneous volume distribution, which is especially concentrated along the water streams. According to the assumed density of 2200 kg m^{-3} (Kargel et al., 2015), our estimated volume ($6229.1 \times 10^3 \text{ m}^3$) turns out to be 11.5×10^9 kg, reaching 3.5 times of the former (Kargel's) estimation. Our volume estimation is similar to that Lacroix (2016) estimated by comparison of SPOT-derived DSMs ($6950 \times 10^3 \text{ m}^3$) with a small error ($\sim 10\%$).

5 Conclusion

Initial multi-satellite observation and assessment were carried out for the catastrophic avalanche induced by the 2015 Gorkha Earthquake in Nepal on April 25. Radar observation by means of PALSAR-2 resulted in two successful ways of backscatter amplitude image and coherence analysis, which are both usable for urgent hazard response to acquire quantitative information, not hindered by frequent cloud cover in those regions during monsoon. Detailed visual interpretation and classification of the sediments with a WV-3 pan-sharpened image revealed the multiple physical properties, which suggest the sequential failure of materials from different sources. The difference between the pre- and post-event DSMs estimated a total sediment volume of $6229.1 \times 10^3 \text{ m}^3$ (11.5×10^9 kg as weight), of which the dominant mass is accumulated along the water streams. Other material-covered surfaces do not have measurable thickness of sediment. The muddy features interpreted in some of them imply high ice and snow content. Coupling further altitude measurements with temporal intervals would clarify the surface lowering by ice/snow melting, for which the water content estimation is invaluable as one of the input data for avalanche simulation and source consideration.



Author contribution

H. Nagai designed the total analysis and discussion. M. Watanabe carried out InSAR coherence calculation and improved the manuscript. N. Tomii organized use of WorldView-3 image. T. Tadono and S. Suzuki managed ALOS-2 observation.

Competing interests

- 5 The authors declare that they have no conflict of interest.

Acknowledgement

We greatly appreciate the financial support from the Council for Science, Technology and Innovation (CSTI), Cross-ministerial Strategic Innovation Promotion Program (SIP), “Enhancement of societal resiliency against natural disasters” (Funding agency: Japan Science and Technology agency). WorldView-3 image was distributed by DigitalGlobe, Inc.

10 WorldView-3 digital surface model was generated by NTTDATA CORPORATION included DigitalGlobe, Inc. ALOS World 3D dataset was generated by NTTDATA CORPORATION and Remote Sensing Technology Center of Japan included JAXA. We also thank members of a J-RAPID team “Investigation of cryo-geohazards in Langtang Valley, Nepal” founded by Japan Science and Technology Agency and those of a non-governmental organization, Langtang Plan, for their valuable information from their post-hazard in-situ survey.

15 References

- Ge, L., Ng, A.H., Li, X., Liu, Y., Du, Z., and Liu, Q.: Near real-time satellite mapping of the 2015 Gorkha earthquake, Nepal, *Ann. GIS*, 21(3), 175–190, doi:10.1080/19475683.2015.1068221, 2015.
- Goda, K., Kiyota, T., Pokhrel, R., Chiaro, G., Katagiri, T., Sharma, K., and Wilkinson, S.: The 2015 Gorkha Nepal earthquake: insights from earthquake damage survey, *Front. Built. Environ.* 1(8), 1–15, doi:10.3389/fbuil.2015.00008, 2015.
- 20 ICIMOD: Geohazards in the aftermath of the 25 April 2015 (12 Baisakh 2072) earthquake, A rapid analysis prepared for the Government of Nepal, 2015. [<http://www.icimod.org/?q=18072>]
- ICIMOD: Villages in Langtang Valley destroyed by landslides and pressure waves during the 25 April 2015 earthquake, 2015. [<http://www.icimod.org/?q=18314>]
- Kargel, J.S., Leonard, G.J., Shugar, D.H., Haritashya, U.K., Bevington, A., Fielding, E.J., Fujita, K., Geertsema, M., Miles, E.S., Steiner, J., Anderson, E., Bajracharya, S., Bawden, G.W., Breashears, D.F., Byers, A., Collins, B., Dhital, M.R., Donnellan, A., Evans, T.L., Geai, M.L., Glasscoe, M.T., Green, D., Gurung, D.R., Heijnen, R., Hilborn, A., Hudnut, K., Huyck, C., Immerzeel, W.W., Jiang, L., Jibson, R., Kaab, A., Khanal, N.R., Kirschbaum, D., Kraaijenbrink, P.D.A., Lamsal, D., Liu, S., Lv, M., McKinney, D., Nahirnick, N.K., Nan, Z., Ojha, S., Olsenholler, J., Painter, T.H., Pleasants, M., KC, P.,



- Yuan, Q., Raup, B.H., Regmi, D., Rounce, D.R., Sakai, A., Shangguan, D., Shea, J.M., Shrestha, A.B., Shukla, A., Stumm, D., van der Kooij, M., Voss, K., Wang, X., Weihs, B., Wolfe, D., Wu, L., Yao, X., Yoder, M.R., and Young, N.: Geomorphic and geologic controls of geohazards induced by Nepal's 2015 Gorkha earthquake. *Science*, 351(6269), doi:10.1126/science.aac8353, 2015.
- 5 Kobayashi, T., Tobita, M., Koarai, M., Otoi, K., and Nakano, T.: Liquefaction Area Associated with the 2011 off the Pacific coast of Tohoku Earthquake, Inferred from Interferometric SAR Coherence Change, *Journal of Geospatial Information Authority of Japan*, 122, 143–151, 2011 (in Japanese).
- Ono, Y. and Sadakane, A.: Natural background of the yak transhumance in the Langtang valley, Nepal Himalaya, *Geographical Reports of Tokyo Metropolitan University*, 21, 95–109, 1986.
- 10 Lacroix, P.: Landslides triggered by the Gorkha earthquake in the Langtang valley, volumes and initiation processes, *Earth, Planets and Space*, 68(46), doi:10.1186/s40623-016-0423-3, 2016.
- Parameswaran, R.M., Natarajan, T., Rajendran, K., Rajendran, C.P., Mallick, R., Wood, M., and Lekhak, H.C.: Seismotectonics of the April–May 2015 Nepal earthquakes: An assessment based on the aftershock patterns, surface effects and deformational characteristics, *J. Asian Earth Sci.*, 111, 161–174, doi:10.1016/j.jseas.2015.07.030, 2015.
- 15 Roy, B., Sathian, B., and Banerjee, I.: Nepal earthquake 2015 – an overview, *J. Biomed. Sci.*, 2(1), 1–2, doi:10.3126/jbs.v2i1.13030, 2015.
- Shiraiwa, T. and Watanabe, T.: Late Quaternary glacial fluctuations in the Langtang Valley, Nepal Himalaya, reconstructed by relative dating methods, *Arctic Alpine Res.*, 23(4), 404–416, doi:10.2307/1551682, 1991.
- Tadono, T., Takaku, J., Tsutsui, K., Oda, F., and Nagai, H.: Status of “ALOS World 3D (AW3D)” global DSM generation, *Proc. of Geoscience and Remote Sensing Symposium (IGARSS), 2015 IEEE International*, 3822–3825, 2015.
- 20 Tamura, M. and El-Gharbawi, T.: Mapping damage in Shinomaki City due to the 2011 Tohoku Earthquake using InSAR coherence change, *Proc. of the 58th Spring Conference of the Remote Sensing Society of Japan*, 29–30, 2015 (in Japanese).
- Yonezawa, C. and Takeuchi, S.: Decorrelation of SAR data by urban damages caused by the 1995 Hyogoken-nanbu earthquake, *Int. J. Remote Sens.*, 22(8), 1585–1600, 2001.




Figure 1: Identified collapsed sediment by ALOS/ALOS-2 images. Difference between PALSAR-2 images of (a) post-quake (April 26, 2015) and (b) pre-quake (December 28, 2014) denotes that the buildings and water stream identifiable by (c) a pre-quake ALOS pan-sharpened image (October 12, 2008) has been covered by the sediments. (d) A three-dimensional view of the ALOS pan-sharpened image overlaid on ALOS World 3D digital surface model.




Figure 2: Normalized coherence decrease around the collapsed area in Langtang Valley. (a) Original output image is processed into two images of focal statistics with (b) 15-m circles for calculating the mean values. High-value parts are denoted on (p) the collapse area, (q) a glacier moraine, and (r) that of a tributary glacier, as well as (s) two places in the valley bottom. The background is an ALOS pan-sharpened image observed on October 12, 2008.




Figure 3: (a) Sediments classified into 15 segments (Seg. 1 to 15) and 3 little-covered segments (Ap. 1 to 3), which were interpreted from a WorldView-3 (WV-3) image acquired on May 8, 2015. (b) Estimation of the sediment volume from the altitude difference between pre-event ALOS World 3D DSM and post-event WV-3 DSM.




Figure 4: Sediment outlines delineated from PALSAR-2 data (purple for amplitude imagery and blue for coherence calculation) and WorldView-3 (WV-3) imagery (orange). The background is hill-shade imagery generated from the WV-3 DSM.



Table 1: Area, thickness, volume, and identified surface features of 15 classified segments of the collapses sediments.

Segment	Area ($\times 10^3 \text{ m}^3$)	Thickness (m)				Volume ($\times 10^3 \text{ m}^3$)	Darkness	Flow or Scatter	Surface character
		Max	Mean	Min.	Max.				
1	54.2	12.0	2.3 ± 1.6	124.5	(57.5 - 204.2)	Dark	Scatter		
2	32.1	9.8	1.7 ± 1.8	55.3	(25.7 - 96.9)	Dark	Scatter		
3	98.2	25.2	2.2 ± 3.0	216.3	(122.3 - 344.7)	Dark	Scatter		
4	19.7	30.2	11.0 ± 7.6	218.0	(190.8 - 246.1)	Dark	Flow		
5	178.5	42.1	20.3 ± 10.6	3612.6	(3365.5 - 3863.4)	Light	Flow	Boulders	
6	85.8	34.6	3.0 ± 5.6	255.5	(195.0 - 347.6)	Light	Flow	Streak	
7	87.1	29.7	2.9 ± 3.2	250.6	(153.3 - 369.2)	Mediam	Flow	Boulders	
8	22.1	11.1	1.7 ± 2.4	37.3	(22.0 - 59.5)	Mediam			
9	46.9	46.7	22.0 ± 13.6	1036.5	(974.5 - 1099.7)	Mediam	Flow	Muddy	
10	75.3	24.3	1.2 ± 3.5	91.5	(72.8 - 114.3)	Mediam		Muddy	
11	114.8	4.9	0.0 ± 0.2	2.1	(0.8 - 4.3)	Mediam	Scatter		
12	87.3	9.6	1.7 ± 1.9	150.7	(75.3 - 258.3)	Dark			
13	116.6	17.1	1.2 ± 2.4	141.6	(81.9 - 250.8)	Dark	Scatter		
14	27.1	1.1	0.0 ± 0.1	0.2	(0.0 - 6.2)	Dark	Scatter		
15	42.4	25.4	0.9 ± 2.6	36.4	(26.1 - 49.6)	Dark	Scatter		
Total	1088.1	46.7		6229.1	(5363.3 - 7314.8)				