

When probabilistic seismic hazard climbs volcanoes: the Mt Etna case, Italy. Part II: computational implementation and first results

Laura Peruzza¹, Raffaele Azzaro², Robin Gee^{1,5}, Salvatore D'Amico², Horst Langer², Giuseppe Lombardo³, Bruno Pace⁴, Marco Pagani⁵, Francesco Panzera³, Mario Ordaz⁶, Miguel Leonardo Suarez⁶, [Giusy Tusa](#)²

¹Istituto Nazionale di Oceanografia e di Geofisica Sperimentale – OGS, Sgonico (TS), 34010, Italy

²Istituto Nazionale di Geofisica e Vulcanologia (INGV), Sezione di Catania – Osservatorio Etneo, 95123, Italy

³University of Catania, Dep. of Biological, Geological and Environmental Science, Catania, 95129, Italy

⁴DiSPUTer, Università “G. d’Annunzio” Chieti-Pescara, 66013, Chieti, Italy

⁵GEM Foundation, Pavia, 27100, Italy

⁶UNAM, Coyoacan 04510, CDMX, Mexico

Correspondence to: L. Peruzza (lperuzza@inogs.it)

Abstract. This paper describes the model implementation and presents results of a probabilistic seismic hazard assessment (PSHA) for the Mt Etna volcanic region in Sicily, Italy considering local volcano-tectonic earthquakes. Working in a volcanic region presents new challenges not typically faced in standard PSHA, which are broadly due to the nature of the local volcano-tectonic earthquakes, the cone shape of the volcano, and the attenuation properties of seismic waves in the volcanic region. These have been accounted for through the development of a seismic source model that integrates data from different disciplines (historical and instrumental earthquake datasets, tectonic fault data, etc. presented in a companion paper Part I, Azzaro et al., 2017), and by the development and software implementation of original tools for the computation, such as a new ground-motion prediction equation and magnitude-scaling relationship specifically derived for this volcanic area, and the capability to account for the surficial topography in the hazard calculation, which influences source-to-site distances. Hazard calculations have been carried out after updating the most recent releases of two widely used PSHA software packages (CRISIS, Ordaz et al., 2013; the OpenQuake-engine, Pagani et al., 2014). Results are computed for short to mid-term exposure times (10% probability of exceedance in 5 and 30 years, Poisson and time-dependent) and spectral amplitudes of engineering interest. A preliminary exploration of the impact of site-specific response is also presented for the most densely inhabited region, and the change in expected ground motion is finally commented. These results do not account for M>6 regional seismogenic sources which control the hazard at long return periods, a limitation of this study. However, by focusing on the impact of M<6 local volcano-tectonic earthquakes, which dominate the hazard at the short to mid-term exposure times considered in this study, we present a different viewpoint that, in our opinion, is relevant for retrofitting of the existing buildings, and for driving impending interventions of risk reduction.

Giusy 12/7/17 13:55

Eliminato: Giusy

Laura Peruzza 12/7/17 13:55

Eliminato: some

Robin Gee 4/7/17 11:15

Eliminato: more

Robin Gee 4/7/17 11:16

Eliminato: most

Laura Peruzza 12/7/17 15:33

Eliminato: using

Laura Peruzza 12/7/17 13:55

Eliminato: softwares

Robin Gee 20/7/17 11:58

Eliminato: referred to

Laura Peruzza 20/7/17 14:13

Eliminato: variability

Robin Gee 14/7/17 17:04

Eliminato: the

Robin Gee 14/7/17 15:18

Eliminato: , in important limit for a PSHA study; we thus acknowledge that rare but strong magnitude earthquakes that dominate the PSHA at longer return periods than the ones we , are mostly interested in. By exploring the

Laura Peruzza 12/7/17 15:52

Eliminato: but

Laura Peruzza 20/7/17 14:14

Eliminato: that we believe is also

1 Introduction

It is well known that volcanoes and earthquakes are associated everywhere, although volcanic seismicity is extremely diversified and is associated with a variety of volcanic processes (Zobin, 2012). In some active volcanic zones, namely the most populated ones, these earthquakes also cause severe damage to urbanized areas and network infrastructure, representing a further source of hazard in addition to the ones posed by the eruptive activity (e.g. Zobin, 2001). Some major worldwide examples of M6-7 earthquakes in different volcanic environments are from Japan, Indonesia, Hawaii, and the Azores Islands (Abe, 1979; Yokoyama, 2001), whilst in the mainland of Europe Mt Etna volcano represents a case where low magnitude events produce local effects of high intensity (Azzaro, 2004; Azzaro et al., 2013). Since seismic hazard is associated with expected earthquakes, why can't we usually pinpoint volcanoes on a hazard map? In general, the effects volcanic earthquakes can be overshadowed by the stronger tectonic regional earthquakes, particularly when long exposure periods are considered. Furthermore, due to their low magnitudes and the high attenuation typically exhibited in volcanic regions, most ground-motion prediction equations (GMPE) are not applicable for such events. We faced these challenges, among others, in the seismic hazard study of Mt Etna, one of the most active volcanoes in a long-lasting inhabited area in the Mediterranean. In a few kilometers it is possible to walk from the ancient Greek and Roman archaeological remains of the coast, to hostile and deserted summit craters 3.3 km above the sea level. While catastrophic earthquakes and tsunamis occur in eastern Sicily on average every 3-4 centuries (Azzaro et al., 1999), building collapse, casualties, and road interruptions due to shallow, light-to-moderate earthquakes (M4-5) happen much more frequently on the flanks of Mt Etna (e.g. D'Amico et al., 2016). These earthquakes are linked to surficial fault sources that breathe with the tectonic stresses and the volcanic dynamics. In recent years, several analyses have been undertaken to estimate the short to mid-term (5-30 years) capability of local faults on Mt Etna to generate damaging or destructive earthquakes. Two main approaches have been explored. The first is a probabilistic seismic hazard assessment (PSHA) based on macroseismic data, which uses a historical probabilistic approach (the "site-intensity approach", see Azzaro et al., 2008; 2016a) to determine the localities prone to high seismic hazard at the local/regional scale. The second is a seismotectonic approach, where historical inter-event times of fault ruptures are investigated and used to generate an earthquake rupture forecast (Azzaro et al., 2012; 2013). In this approach, Poissonian occurrence probabilities of major earthquakes have been determined, as well as time-dependent occurrence probabilities using a renewal processes that takes into account the time elapsed since the last event. Both approaches have found that the local faults significantly contribute to the seismic hazard around Mt Etna with respect to the larger regional events, when short investigation times are considered. In 2012 a new project started, namely the DPC-INGV V3 Project (Azzaro et al., 2016b), with one of its targets being a new PSHA for the Etna region, due to local volcano-tectonic earthquakes. Working in the Mt Etna region presents new challenges not typically faced in standard PSHA. These are due to i) the nature of the local volcano-tectonic earthquakes, which are low-magnitude (partially out of the applicability range of most GMPEs) and have large ruptures compared to those predicted by commonly used magnitude scaling relationships (MSR), ii) the cone shape of the volcano, where events are

- Robin Gee 20/7/17 10:43
Eliminato: everywhere ...sociated everyw... [1]
- Laura Peruzza 20/7/17 14:16
Eliminato: varie
- Raffaele Azzaro 18/7/17 10:02
Eliminato: and ...n some active volcano... [2]
- Robin Gee 20/7/17 10:48
Eliminato: indeed
- Raffaele Azzaro 18/7/17 11:47
Eliminato: Azzaro, 2004
- Robin Gee 20/7/17 11:53
Eliminato: referring...n to [3]
- Laura Peruzza 19/7/17 15:58
Eliminato: geodynamic
- Robin Gee 20/7/17 10:49
Eliminato: ...,are from...rom Japan, Indon... [4]
- Laura Peruzza 20/7/17 14:19
Eliminato: , exacerbated by thea high rate of occurrence
- Robin Gee 20/7/17 10:45
Eliminato: goes with the
- Raffaele Azzaro 18/7/17 12:32
Eliminato: The
- Robin Gee 20/7/17 10:46
Eliminato: of these shallow... volcanic [5]
- Raffaele Azzaro 17/7/17 17:10
Eliminato: in the region
- Robin Gee 20/7/17 10:46
Eliminato: ,
- Raffaele Azzaro 17/7/17 17:26
Eliminato: temples...of the coast, to hostil... [6]
- Robin Gee 4/7/17 11:18
Eliminato: p

located within the volcanic edifice above the sea level, and therefore the topography (elevation) of Mt Etna must be considered, which in turn affects source-to-site distances in the hazard computation, iii) the attenuation properties of seismic waves in the Mt Etna region, where events exhibit rapid attenuation particularly at high frequencies, and finally iv) heterogeneities in rock properties within the volcanic body, and thus proxies simply based on slope or surface geological mapping are not adequate to represent reliable site-specific effects. To address these challenges, we used two PSHA software packages (CRISIS, Ordaz et al., 2013; the OpenQuake-engine, Pagani et al., 2014) and developed new software functionalities to incorporate the topographic surface into the hazard calculation by modelling sources and sites above the sea level. We also derived new empirical relationships specifically for Mt Etna, such as a MSR (described more in detail in the companion paper, Azzaro et al., 2017, hereinafter referred to as Part I), and a GMPE presented here. In this paper we summarize the source model, discuss the model implementation, new GMPE and software functionalities, and finally present the hazard results. We hope the results of this study may be integrated into a national, more traditional, regulation framework (e.g., Stucchi et al., 2011), for having realistic and useful ground motion prediction maps devoted to urban planners and structural designers.

2 Seismic source model: conceptual components

The seismic source modelling at Mt Etna accounts for three different levels of increasing complexity, and sources are modelled using distributed seismicity as well as fault sources. The source model accounts for some basic assumptions behind the physical processes driving earthquake occurrences, which in our volcanic area refer to the brittle failure of rocks under tectonic stress producing volcano-tectonic earthquakes along well-known surface breaking faults. In particular: i) the damaging earthquakes at Mt Etna feature very shallow foci; ii) these shocks, which are mainly concentrated on the southeastern flank of Mt Etna, occur with about decennial frequency (see for example, Azzaro et al., 2012; 2013; Sicali et al., 2014) with or without synchronous volcanic activities; iii) the last major events and interseismic periods have been monitored by a dense, high-quality instrumental local network whose geometry and characteristics have essentially remained unchanged during in the last two decades (Alparone et al., 2015).

For a full description of the individual model components and the process of defining seismic sources, we refer the reader to Part I. Different seismic sources were defined for representing the shallow volcano-tectonic seismicity at Mt Etna, after checking that a few years of high quality seismic monitoring, during an interseismic interval, can be representative of the long-term seismic rates of volcano-tectonic faults; this simplification is supported by about two centuries of detailed field observations and chronicles, describing the seismotectonic evidence, and by the deformation rates derived from geodesy. If we accept this working hypothesis, we can parameterize seismic sources by extrapolating decennial datasets. We can also model by means of point sources faults that are still “unknown” as they are not recognised/mapped at the surface, and we may compute earthquake probabilities using any interarrival time/magnitude-frequency distribution (FMD) thus abandoning the requirements of independence and stationarity of events, needed by the traditionally used Poisson process.

Robin Gee 4/7/17 11:18

Eliminato: effects

Raffaele Azzaro 18/7/17 12:44

Eliminato: 3

Laura Peruzza 19/7/17 16:08

Spostato in giù [3]: For a full description of the individual model components and the process of defining seismic sources, we refer the reader to Part I.

Robin Gee 4/7/17 11:20

Eliminato: concerning the engine of earthquake occurrences

Raffaele Azzaro 17/7/17 17:14

Eliminato: which

Raffaele Azzaro 18/7/17 12:50

Eliminato: a

Raffaele Azzaro 17/7/17 17:14

Eliminato: can due

Robin Gee 20/7/17 10:53

Eliminato: ,

Raffaele Azzaro 17/7/17 17:12

Eliminato: known as volcano-tectonic earthquakes, or the movement of fluids within the volcano, such as volcanic tremor

Raffaele Azzaro 18/7/17 12:57

Eliminato: , shallow focus

Raffaele Azzaro 18/7/17 12:58

Eliminato: are volcano-tectonic earthquakes

Raffaele Azzaro 18/7/17 12:58

Eliminato: earthquakes

Robin Gee 4/7/17 11:21

Eliminato: which

Robin Gee 4/7/17 11:21

Eliminato: are

Laura Peruzza 19/7/17 16:08

Spostato (inserimento) [3]

Laura Peruzza 19/7/17 16:09

Eliminato: In Part I, we describe in detail the d

Laura Peruzza 19/7/17 16:10

Eliminato: . These sources were defined

Raffaele Azzaro 17/7/17 17:27

Eliminato: naturalistic

Laura Peruzza 19/7/17 17:39

Eliminato: MFD

Robin Gee 4/7/17 11:21

Eliminato: independency

The sources at Mt Etna take into account the huge amount of available geological, historical, seismological and geodetic data. The three types of seismic sources depicted in Part I are as follows (see Figure 1 and concept scheme in Figure 2):

• *area seismic sources* (Figure 1a) which are zones of distributed (uniform) seismicity. These encompass the best-known fault systems on the flanks of Mt Etna. They are defined both in CRISIS and the OpenQuake-engine by a horizontal planar surface, modelled as a series of point sources with spatially extended ruptures. This approach is the same used by the actual seismic hazard map of Italian regulation (MPS04, Stucchi et al., 2011), where the whole volcanic body is enveloped in a single polygonal area;

• *fault sources* (Figure 1b) which model the main tectonic structures. The geometries are based on surface ruptures and other geological and geophysical investigations. Faults are modelled in the OpenQuake-engine by a mesh of points defined by top and bottom (and optionally middle) edges whose 3D geometry may change in dip and width and extended ruptures float along strike. In CRISIS, faults can be set as planes of given coordinate vertices;

• *point sources* (Figure 1c) which are used to represent distributed (gridded, non-uniform) seismicity. The distributed seismicity is defined in a common manner by CRISIS and the OpenQuake-engine, using point sources with spatially extended ruptures and variable properties (e.g. seismicity, depth).

In the case of Mt Etna, the sources extend above the sea level to model the earthquakes within the volcanic edifice, and also the faults intersect the topographic surface.

These sources are combined together to form alternative seismic source models. Three source model branching levels are defined, in order of increasing complexity, to represent the epistemic uncertainties (Figure 2):

• *Source Model Level 1* is composed of area sources only. Four zones of uniform seismicity are parameterized by Gutenberg-Richter (GR) *FMDs* calibrated on the best quality instrumental catalogue (see Section 4.1 in Part I) during an inter-seismic period that is considered representative of the long-term seismic behavior observed since the XIXth century. Seismicity rates are extrapolated until the maximum magnitude observed in the historical period (M_{max} 5.2), and effective depths are estimated by the analyses of strain release profiles. The values of parameters entered in both the OpenQuake-engine and CRISIS are given in Table 1.

• *Source Model Level 2* combines major earthquakes ($M > 4.5$) that are assigned to faults only, with background seismicity that is assigned to area sources as in Level 1 (modelled up to M_{max} 4.5). The *FMDs* of faults are Gaussian distributions peaked to the characteristic earthquake models; rates are branched, based on the historical observations only, or constrained by geometrical and geological-kinematic considerations on fault size and slip rate (observed and calculated mean recurrence time T_{mean} and maximum magnitude M_{max} in Table 2; see Pace et al., 2016 for the method; Part I for results obtained at Mt Etna). In Table 2 we summarize the input data and the results in terms of probabilities of occurrence of the characteristic earthquake, following a memory-less process (Poisson), or introducing the time-dependency of the last event of a Brownian Passage Time model, for both the branches, historical and geological-kinematic. Note that the Pernicana Fault (PF) is always modelled as GR, not having historical observations supporting the choice of a characteristic earthquake model.

Raffaele Azzaro 17/7/17 17:28

Commenta [1]: È una ripetizione

Laura Peruzza 19/7/17 16:01

Eliminato: are set up with a great degree of detail and complexity, and

Laura Peruzza 19/7/17 16:12

Eliminato: ; they derive from historical observations and from the extensive real-time monitoring available for this area

Laura Peruzza 19/7/17 16:12

Eliminato: -

Raffaele Azzaro 17/7/17 17:29

Commenta [2]: In Part I l'acronimo è scritto al contrario

Laura Peruzza 19/7/17 17:39

Eliminato: MFD

Robin Gee 20/7/17 11:02

Eliminato: MFD

Raffaele Azzaro 17/7/17 17:30

Eliminato: Alparone et al., 2015

Laura Peruzza 19/7/17 17:40

Eliminato: MFD

Concerning the geological conditions, the Mt Etna volcanic edifice overlies a thick sedimentary substratum with strong lateral heterogeneities (see e.g. Branca et al., 2011; De Gori and Chiarabba, 2005). The foci of the shallow events (focal depth less than 5 km) fall into a depth range above mentioned sedimentary substratum; therefore this hypocentral location affects both the seismic scaling laws (relationship of released seismic energy and size of the source) and the wave propagation phenomena (Patanè et al., 1994; Giampiccolo et al., 2007; see Langer et al., 2016 for a more detailed discussion). Strong differences between shallow and deep events (focal depth greater than 5 km) at Mt Etna can be clearly identified just looking at the waveforms. For similar magnitude and distance, the shallow events have more low frequency content than the deeper ones, where conversely the high frequencies prevail (i.e., Tusa and Langer, 2016). The distinctiveness of the shallow events makes the application of common ground-motion prediction equations used for tectonic areas questionable and inappropriate.

For the purposes of DPC-INGV V3 Project, we derived a local GMPE focusing on the shallow events at Mt Etna and using the high quality data collected by the numerous seismic broadband stations that have been operating in eastern Sicily since 2006. We used the same sample of data as Tusa and Langer (2016, hereafter TL16) the original GMPE developed for this project, but this time consider a different distance metric (hypocentral distance instead of epicentral distance as required to incorporate topography into the calculation, see Section 4). The dataset consists of a set of 1200 three-component recordings acquired during 38 events in the magnitude range $3.0 \leq M < 4.3$ with hypocentral distances between 0.5 and 100 km. Moreover, 95% of the hypocenters are shallower than 2.5 km. The data were checked visually at all stations to exclude traces with electronic glitches, and with phenomena of amplitude saturation. As a first step in the processing, the digitized velocity time histories of the horizontal components were baseline corrected, removing offset and the linear trend from the data, and instrument corrected obtaining ground velocity in units of m/s. They were then band-pass filtered using corner frequencies of 0.1 and 25 Hz for the high-pass and low-pass filtering, respectively. The weak motion velocity data were differentiated to calculate acceleration time series. The peak amplitude values of the ground acceleration (PGA) were read on the traces resulting from the geometric mean of the horizontal components (Akkar and Bommer 2010; Akkar et al. 2010; Bindi et al. 2011). For an extensive description of statistical characteristics of the data set, for example, in terms of number of data-magnitude, number of data-recording site class, and distance-magnitude distributions, we direct the readers to TL16. In order to compare our data to those recorded in other regions in Italy (in particular the Italian ITA10 equation by Bindi et al., 2011), our empirical GMPE follows the simplified version of the formulation proposed by Boore and Atkinson (2008):

$$\text{Log}(Y) = a + b_1 M + b_2 M^2 + [c_1 + c_2 (M - M_{ref})] \text{Log} \left(\sqrt{R^2 + h^2} / R_{ref} \right) + c_3 \left(\sqrt{R^2 + h^2} - R_{ref} \right) + e_i S_i + \sigma_T \quad (1)$$

where M_{ref} is a reference magnitude for magnitude dependence of geometric spreading (here fixed to the mode value of the dataset, equal to 3.6), R is the hypocentral distance in km, R_{ref} is reference distance at which the near source predictions are pegged, and h is an additional parameter, addressed to as "pseudo depth", incorporating all the factors that tend to limit or reduce motion near the source (Joyner and Boore 1981). The multiplier of the logarithmic distance term accounts for the magnitude-dependent ground motion decay and controls the saturation of high-frequency ground motions at short distances.

Laura Peruzza 12/7/17 16:30

Eliminato: INGV-

Raffaele Azzaro 17/7/17 17:31

Eliminato: of the Rete Sismica Permanente della Sicilia Orientale (RSPSO)

Robin Gee 13/7/17 14:06

Eliminato: the

Giusy 12/7/17 13:55

Eliminato: a

Giuseppina Tusa 27/6/17 12:49

Eliminato: a

Giusy 12/7/17 13:55

Eliminato: .

S_i indicates the soil conditions, with i standing for the soil classes A, B, C, and D defined in the EC8 building code. The S_i variables of Boolean type are set to unity if the corresponding soil class is met at a site, whereas the S_i for all other classes is zero. Finally, σ_T represents the total standard deviation, which is the uncertainty in $\text{Log}(Y)$. The basic difference with TL16 is the distance metric, measured with respect to the hypocenter instead of the epicenter. This change allows accounting for the elevation of the seismic stations, which may vary in the range of about 2.5 km, a relevant difference, in particular for areas close to the epicenter.

The coefficients of our model, including the pseudo depth h as well, were estimated applying the classical non-linear least-squares Marquardt-Levenberg algorithm as implemented in MATLAB. The coefficients of the model are computed by using an iterative least squares estimation, with specified initial values. In particular, we tested different starting models in order to evaluate their effects on the solution, and at the same time, to select those values towards which the several inversions converged. The equations are derived from the regression analyses for horizontal PGA and 5% damped spectral acceleration (PSA) at several periods from 0.1 to 10 s. The regression coefficients and their 95% confidence intervals for PGAs are reported in Table 3 (for PSAs see the Electronic Supplement). The value of coefficient c_3 , which stands for inelastic attenuation, is very close to zero and could be potentially omitted from the functional form in eq. (1). It has a minimal influence on the dependent variable values estimated through the obtained regression model. The standard deviation obtained by bootstrap analysis is given too. The bootstrap bypasses problems in estimating uncertainties of model parameters obtained in non-linear inversion, which is based on the Jacobian matrix and has the advantage of being applicable without a priori knowledge of the distribution of the underlying parent population. Compared to standard methods, the bootstrap yields a more robust and conservative estimation of parameter uncertainties. Here, in order to assess the stability of estimated regression coefficients, we resampled our data set 1000 times and applied the same regression models as before. Each application gives a different set of regression coefficients and we calculate the statistics over our 1000 sets of coefficients.

The total standard deviation, σ_T , can be split into two terms:

$$\sigma_T = \sqrt{\sigma_{eve}^2 + \sigma_{intraeve}^2} \quad (2)$$

where σ_{eve} and $\sigma_{intraeve}$ are the inter-event and intra-event error components, respectively representing the error variability for different stations recording the same event, and the error variability for different earthquakes recorded by the same station. Similarly, if the variability among recording sites is taken into account, the total standard deviation of $\text{Log}(Y)$ in Eq. (1) is given by:

$$\sigma_T = \sqrt{\sigma_{sta}^2 + \sigma_{intraSta}^2} \quad (3)$$

where σ_{sta} and $\sigma_{intraSta}$ represent the inter-station and intra-station component of the variance. We estimated the inter-group (inter-event and inter-station) and the intra-group (intra-event and intra-station) variance - understood here in terms of mean square errors - for each attenuation model, by applying the "Analysis Of Variance" test. We observe that the horizontal PGA

Giuseppina Tusa 27/6/17 12:53

Eliminato:

Giuseppina Tusa 28/6/17 15:00

Eliminato: and

Robin Gee 13/7/17 14:11

Eliminato: in

Giusy 12/7/17 13:55

Eliminato: .

Robin Gee 13/7/17 14:17

Eliminato: However, it has a forgettable

Giuseppina Tusa 28/6/17 16:16

Eliminato: (by resampling our data set 1000 times)

has similar σ_{eve} and σ_{sta} values, whilst the spectral acceleration shows, in general, higher inter-station variability than the inter-event component, suggesting that the local site effects are the main source of ground-motion variability for our data.

In Figure 3 we compare the predictions of horizontal PGA obtained in this study (coefficients reported in Table 1) with those derived by TL16 for shallow seismic activity at Mt Etna, and by Bindi et al. (2011, referred as ITA10) for the whole Italian national territory. Differences between the epicentral (TL16) and hypocentral versions of the GMPE (red and blue curves, respectively) are most evident for source-to-site distances < 5 km, where the hypocentral version of the GMPE predicts higher accelerations. ITA10 (green curves) shows evident differences related to the flat part of the attenuation curves at short distances that goes from 0 to 10 km and more. The extension of this plateau depends critically on the h parameter, and focal depths in ITA10 are larger than the one selected for Mt Etna, thus leading to a higher h coefficient. Note that ITA10 is based on 793 records from 99 events and 150 stations, collected on the whole Italian territory; our data set offers at least the same or even a better statistical stability, both from the total number of records (1200) and coverage (records per event, records per station and homogeneity from a seismo-tectonic point of view). From a practical point of view, the use of ITA10 strongly overestimates the PGA for shallow earthquakes at Mt Etna as it predicts values which differ by a factor of about 3 near the source (distances $< 2-3$ km) and much higher values (1-2 order of magnitude) at distances of 5-50 km. A quite different picture is obtained when spectral accelerations are taken into account, for example at $T > 0.5$ s, where ITA10 shows an underestimation of ground shaking (see Figure 1 in the Electronic Supplementary Material). This is due to the fact the spectra of shallow events at Mt Etna are richer in low frequencies than the earthquakes normally used in GMPE, that are located at depth into the crystalline basement.

The GMPE equations obtained by this study have been implemented in the software packages used for our analyses, and will be referred to hereinafter as the ETNAhy GMPE model. In CRISIS, the ETNAhy GMPE has been used by means of precompiled attenuation tables: an example for PGA, SA at 0.2, 0.4 and 1.0 s for soil type A is given as supplementary material. Note that the magnitude range of applicability (stated in this sample table at 2.6-5 covers values usually not represented by standard GMPEs. In the OpenQuake-engine, ETNAhy has been added to the library of GMPEs (<https://github.com/gem>), which also includes TL16, the version for R_{epi} . Verification of the implementation was performed by testing the expected mean and standard deviation output of the GMPE against a table of expected values provided by the authors for different combinations of input variables (e.g. magnitude, distance, and V_{30}).

Table 3: Coefficients of Eq. (1) for the prediction of PGA_h (gal) for the GMPE in this study. CI95 indicates the confidence intervals at 95% confidence level. R^2 is the determination coefficient. σ_{eve} and σ_{sta} inter-event and inter-station terms of the errors, respectively. BS_{mean} and $BS\sigma$ are the mean value and the standard deviation of each coefficient, respectively, estimated by applying the bootstrap technique.

a	b_1	b_2	c_1	c_2	h	c_3	e_B	e_D	R^2	σ_{eve}	σ_{sta}	σ_T
---	-------	-------	-------	-------	---	-------	-------	-------	-------	----------------	----------------	------------

Giusy 12/7/17 13:55

Eliminato: seismotectonic

Giuseppina Tusa 28/6/17 17:37

Eliminato: about the same values

Giuseppina Tusa 28/6/17 17:39

Eliminato: but

Giusy 12/7/17 13:55

Spostato (inserimento) [1]

Robin Gee 13/7/17 14:27

Eliminato: a

Laura Peruzza 19/7/17 16:24

Eliminato: -

Laura Peruzza 12/7/17 13:55

Spostato in giù [2]: Verification of the implementation was performed by testing the expected mean and standard deviation output of the GMPE against a table of expected values provided by the authors for different combinations of input variables (e.g. magnitude, distance, and V_{30}).

Giuseppina Tusa 28/6/17 16:25

Eliminato: In the OpenQuake-engine, ETNAhy has been added to the extensive library of GMPEs where it is included in the file `tusa_langer_2016.py` (https://github.com/gem/eq-hazardlib/blob/master/openquake/hazardlib/gsim/tusa_langer_2016.py), which also includes TL16, the version for R_{epi} .

	0.329	0.105	0.076	-2.111	0.039	1.553	0.006	0.450	0.457	0.853	0.228	0.222	0.394
<i>CI95</i>	-1.993	-1.136	-0.097	-2.376	-0.125	0.084	0.003	0.337	0.309				
	2.651	1.346	0.248	-1.847	0.204	3.190	0.010	0.562	0.604				
<i>BS_{mean}</i>	0.381	0.073	0.080	-2.106	0.040	1.174	0.006	0.455	0.463				
<i>BS_s</i>	0.039	0.554	0.078	0.140	0.078	2.780	0.002	0.076	0.084				

4 Accounting for topography

Another implementation introduced in this study concerns the capability of taking into account the surface topography (elevation) in PSHA calculation. Typically in PSHA, the sites of the hazard computation are defined in terms of their geographic coordinates on a planar surface representative of the sea level. This implies that the elevations of the sites are assumed to be zero, and the source-to-site distances in the PSHA calculation are computed accordingly. Usually this is an appropriate approximation because the actual elevations of the sites are small compared to the depths of the sources. However, in the case of Mt Etna, this approximation cannot be made. Here, the earthquakes are shallow (mostly within the upper 5 km, and some even above the sea level inside the volcanic edifice) and the elevation of the volcano increases sharply moving from the coast to the central craters, which are more than 3 km above sea level.

A cross section of Mt Etna is shown in Figure 4, illustrating how the surface topography effects source-to-site distances. In this example, the distance Rhypto – as used by the GMPE in this study – increases when the topographic surface is included because the site elevation is increased. Note that for some source-to-site combinations, a straight path from the source to the site passes in the air above the free surface (for example if the site is at the very top of Mt Etna and a shallow source is located a few kilometers away from the base), and therefore cannot be realistically followed by seismic waves. However, we find that the curvature of the topography is not pronounced enough (i.e. the slope of the topography changes gradually at the scale of the volcano), to cause a significant difference between a linear source-to-site path and a path that follows the free surface topography, and therefore we accept the approximation of a linear source-to-site path that the influence of the topographic surface we describe here is purely a geometrical one, and should not be confused with topographic site effects, where seismic waves are amplified in the vicinity of summits (see, for example, Imperatori and Mai, 2015 and references therein); further analyses of the topographic effects in the residuals of the ground motion model, and betterments in the rupture to site distance metric are promising, but out of the scope of this paper.

In order to correctly compute the source-to-site distances in the hazard calculation, we implemented the possibility to model a 3D topographic surface into both software packages. In CRISIS, this functionality has been added since the release V1.0 of 2015, by means of a specific layer that represents the topography of the study area. A digital elevation model, given in a gridded data file, can be uploaded and the sites elevations are automatically computed on this surface (Figure 5). The capability in the OpenQuake-engine has been available since early 2017 (V2.3.0), and enables the user to specify the sites of

- Giusy 12/7/17 13:55
Spostato in su [1]: The GMPE equations obtained by this study have been implemented in the software packages used for our analyses, and will be referred to hereinafter as the ETNAhy GMPE model. In CRISIS, the ETNAhy GMPE has been used by means of precompiled attenuation tables: an example for PGA, SA at 0.2, 0.4 and 1.0 s for soil type A is given as a supplementary material. Note that the magnitude range of applicability (stated in this sample table at 2.6-5.3) covers values usually not represented by standard GMPEs. In the OpenQuake-engine, ETNAhy has been added. [7]
- Laura Peruzza 19/7/17 16:24
Eliminato: Verification of the implement... [8]
- Laura Peruzza 12/7/17 13:55
Spostato (inserimento) [2]
- Laura Peruzza 19/7/17 16:25
Eliminato: .
- Robin Gee 13/7/17 14:25
Eliminato: ,)
- Robin Gee 4/7/17 11:30
Eliminato: we have done
- Laura Peruzza 12/7/17 13:55
Eliminato: done
- Robin Gee 4/7/17 11:53
Eliminato: for ...n this study concerns the ... [9]
- Laura Peruzza 11/7/17 14:49
Eliminato: The influence of the topograph... [10]
- Robin Gee 5/7/17 10:38
Eliminato: A schematic diagram is shown ... [11]
- Laura Peruzza 11/7/17 15:56
Eliminato: a linear
- Robin Gee 13/7/17 20:32
Eliminato: the strait
- Laura Peruzza 11/7/17 15:57
Eliminato: cannot be constructed without
- Robin Gee 13/7/17 20:32
Eliminato: is not the one that can be follo... [12]
- Laura Peruzza 11/7/17 15:59
Eliminato: . An... (for example of this wo... [13]
- Robin Gee 13/7/17 20:33
Eliminato: In a schematic representation ... [14]
- Robin Gee 14/7/17 15:10
Formatato: Non Barrato
- Robin Gee 4/7/17 16:02
Eliminato: . . [15]
- Laura Peruzza 12/7/17 13:55
Eliminato: Etna

the hazard calculation in terms of longitude, latitude, and depth coordinates with respect to the sea level, for example, in the form of a csv file. In both [software packages](#), sources may also be defined above the sea level, using the convention of negative values for indicating elevations above sea level.

This new functionality can be extended to other regions, although is most appropriate in cases when the inclusion of topography is relevant to hazard (i.e. shallow sources with respect to the topographic elevation, see for example Peruzza et al., 2016), and source locations are well-constrained with respect to the sea level, as is the case at Mt Etna. In theory, site locations may also represent surfaces that are not exposed (e.g. the sea bottom, or bedrock lying below alluvial deposits), thus opening new potentialities for integrating site-specific response into hazard computation. As incremented capabilities may also introduce new problems for Mt Etna analyses (i.e. how to account correctly for bedrock response, if we are not in free-field conditions), we will accept the simplification that the topographic surface represents reference sites on bedrock.

We performed sensitivity tests at Mt Etna to compare the software performances, and to show the contribution of topography to the hazard. CRISIS and the OpenQuake-engine behave the same in the simplest source formulation, e.g. area and point sources, and very similarly when complex faults are treated. To demonstrate the influence of topography, we use the same area sources as this hazard assessment but assign all of them the same [FMD](#) and a depth of 2.5 km, with the seismogenic layer extending from 0 - 5 km (Figure 6). We find that including topography causes an increase in source-to-site distance, and therefore a decrease in hazard that locally reaches about 50% of the values compared to the model that does not include topography. This effect is most pronounced in the regions of maximum elevation, notably the sources closest to the central craters (i.e. [PF](#), the Pernicana area source) 

20 5 Accounting for site-specific response

We investigated the site-specific seismic response of the most densely populated area of [the](#) SE flanks at Mt Etna by adopting the commonly used horizontal to vertical spectral ratio techniques that evaluate the site response properties using both earthquake (HVSr) and ambient noise (HVNR) as input signals ([Nogoshi and Igarashi, 1971](#); [Nakamura 1989](#); [Lermo and Chavez-Garcia, 1993](#)). [Although these methodologies are commonly applied in areas showing strong impedance contrast and/or minor lateral heterogeneities, they have been widely applied with valuable results in volcanic areas characterized by a complex geologic setting \(e.g. \[Lombardo et al., 2006\]\(#\); \[Panzer et al., 2013\]\(#\); \[2016\]\(#\); \[2017\]\(#\); \[Rahpeyma et al., 2016\]\(#\)\).](#)

The HVSRs were performed [by](#) selecting 30 local events that occurred in the volcanic area with $M_L > 2.5$; records [were](#) extracted from the INGV - Osservatorio Etneo database, while location and magnitude [were](#) taken from the INGV - Osservatorio Etneo bulletins. Recorded earthquakes were base-line corrected, with the purpose of removing spurious offsets, and band-pass filtered in the range 0.08-20 Hz, with a fourth order causal Butterworth filter. The analysis was performed by using 20s time windows, starting from the S-wave onset, including part of the coda and using a 5% cosine-tapered window. Fourier spectra were smoothed using a Konno-Ohmachi filter ([Konno and Ohmachi 1998](#)) and the selected time window was

Laura Peruzza 12/7/17 13:55

Eliminato: softwares

Laura Peruzza 19/7/17 17:40

Eliminato: MFD

Robin Gee 20/7/17 11:11

Eliminato: .

Laura Peruzza 12/7/17 14:10

Eliminato:

Robin Gee 20/7/17 11:11

Eliminato:

Laura Peruzza 19/7/17 16:28

Formattato: Non Evidenziato

Laura Peruzza 19/7/17 16:28

Formattato: Non Evidenziato

Robin Gee 13/7/17 17:36

Eliminato: were

Robin Gee 20/7/17 11:13

Eliminato: are

Robin Gee 20/7/17 11:13

Eliminato: are

Laura Peruzza 19/7/17 16:28

Formattato: Non Evidenziato

compared with the pre-event noise, in order to select good quality data based on the signal/noise ratio. For each recording, only those signals with $s/n \geq 3$ were considered for analysis. The spectral ratios were evaluated at each station for the selected events and a geometric mean of all spectral ratios were computed to obtain the mean HVSr curve and the corresponding standard deviation. The resulting experimental HVSr were inverted through ModelHVSr Matlab routines (Herak, 2008) in order to compute theoretical HVSrs in homogeneous and isotropic layers. For the 19 considered seismic stations at Mt Etna (stations locations are shown in Figure 7a), the stratigraphic sequence and local velocity model were made by integrating literature information and observations (Azzaro et al., 2010; Branca et al., 2011; Branca and Ferrara, 2013; Panzera et al., 2011; Panzera et al., 2015; Priolo, 1999). The soil models consist of a number of visco-elastic layers, stacked over a half-space, each of them being defined by the thickness (h), the velocity of the body waves (V_p and V_s), the density (ρ), and the Q-factor, which controls the inelastic properties. The code assumes that incoming waves are travelling vertically and considers that horizontal and vertical motions at the bedrock have no amplification. The HVSr at the surface is then obtained as the ratio between the theoretical transfer functions of S and P waves (Herak, 2008). The obtained HVSr output models were then used as input for the amplification function (AF) for 14 seismic stations. Five stations, showing lack of convergence between the experimental and theoretical model, were removed. The AFs were computed through frequency-domain calculations, using the program SiteAmp by Boore (2003) that convert a velocity and density model into site amplifications. In particular, the Fortran code calculates the Thomson-Haskell plane SH-wave transfer function for horizontally stratified constant velocity layers at a specific incidence angle within a uniform velocity half-space. The input parameters are the V_s , the density (ρ), and Q. The half-space is set at the deepest measured layer and the solution is exactly equivalent to the solution computed by the equivalent linear site response program SHAKE for linear modulus reduction and damping curves (Schnabel et al., 1972). The code computes the amplifications either at specified frequencies or at frequencies corresponding to the “breakpoints” in the velocity model.

The obtained AF were grouped, according to their different “spectral shape” into four classes, by considering the frequency at which the dominant HVSr peak occurs, using the following criteria:

- ET-1 class: Flat spectral ratios showing amplitude values not exceeding 2 units (including standard deviation);
- ET-2 class: HVSr having fundamental period $T \leq 0.2$ s with amplitude exceeding 2 units;
- ET-3 class: HVSr with fundamental period $0.2 < T \leq 1.0$ s with amplitude exceeding 2 units;
- ET-4 class: HVSr showing broadband amplitude exceeding 2 units;

The class’ AF is obtained by averaging the AFs of all the stations included in the class (Figure 7b).

The European project Site EffectS assessment using Ambient Excitations (SESAME, 2004) found that the ambient vibration method is a reliable alternative approach to using earthquake records especially for estimating the fundamental frequencies of a site. For this reason we performed a comparison between experimental HVSrs and HVNRs obtained at the seismic stations located all around the volcano. The good matching obtained encouraged us to consider the ambient noise signal as a valid seismic input, to be used to define the site fundamental frequency. We therefore proceeded to obtain the fundamental period classification in a wide sector of the lower eastern flank of Mt Etna that includes 14 municipalities and many villages

Robin Gee 20/7/17 11:14

Eliminato: in inset map of

Laura Peruzza 19/7/17 16:28

Formattato: Non Evidenziato

Robin Gee 13/7/17 17:28

Eliminato: , t

Laura Peruzza 12/7/17 14:11

Eliminato: The incoming waves are assumed to be travelling vertically and assuming that horizontal and vertical motions at the bedrock have no amplification, the HVSr at the surface is then obtained as the ratio between the theoretical transfer functions of S and P waves.

Laura Peruzza 19/7/17 16:28

Formattato: Non Evidenziato

Robin Gee 13/7/17 21:17

Eliminato: stated

Laura Peruzza 19/7/17 16:28

Formattato: Non Evidenziato

Robin Gee 20/7/17 11:16

Eliminato: in

Laura Peruzza 19/7/17 16:28

Formattato: Non Evidenziato

Laura Peruzza 12/7/17 14:12

Eliminato: The good matching obtained by the comparison of experimental HVSrs and HVNRs at the seismic stations located all around the volcano encouraged us to consider the ambient noise signal as a valid seismic input, to be used to define the fundamental frequency of a site.

Raffaele Azzaro 17/7/17 17:39

Eliminato: study area located

Raffaele Azzaro 17/7/17 17:39

Eliminato: along

Raffaele Azzaro 17/7/17 17:40

Eliminato: , from North to South, the

and rural settlements (Figure 7a, coloured dots). As highlighted in Part I, this area is the most affected by strong shaking due to the seismogenic activity of the Timpe faults, and hence it is an appropriate choice for investigating the role of site-specific seismic responses. The fast and inexpensive HVNR technique has been performed by 130 georeferenced noise measurements recorded using a three components velocimeter, on a grid of sites quite homogeneously spaced at about 1x2 km distance. All the HVNRs in the present study were performed using time series of 30 minutes length, with a sampling rate of 128 Hz. Signals were processed by considering time windows of 30 s, selecting the most stationary part, excluding transients associated to very close sources. In this way, the Fourier spectra were calculated in the frequency range 0.1-30.0 Hz and smoothed using a proportional 20% triangular window. Following the criteria suggested by SESAME, only the spectral ratio peaks having amplitude greater than two units, in the frequency range 0.5-10 Hz, were considered significant. The obtained HVNRs were manually classified and repeatedly checked into the four classes of predominant period previously identified (Fig. 7).

A preliminary predominant-period site classification along the Mt Etna eastern flank is finally attempted, to overcome the one based on average shear wave velocity classification of the upper 30 m (V_{s30}). We mapped in the format required by CRISIS the coefficients to be used in site-specific seismic hazard map, after interpolation of amplification factors at some spectral ordinates done by Nearest Neighbour algorithm (Figure 8). According to Barani and Spallarossa (2016), this soil hazard method can be considered a hybrid probabilistic-deterministic method, and it may be useful to provide a first representation of seismic soil hazard at the large scale.

6 Results

We compute the hazard at Mt Etna for the 3 source branching levels (depicted in Figure 2), using the ETNAhy GMPE and the MSR derived specifically for this volcanic region as described in Section 3 and Part I, respectively. Computations are for short-to-mid exposure periods (10% exceedance probability in 5 and 30 years). Seismic hazard maps refer to rock conditions, where $V_{s30}=800$ m/s (Figures 9-11), and exploratory site-specific results are also shown (Figure 12).

The results obtained with the OpenQuake-engine in terms of PGA are shown in Figures 9 and 10. For a 5 year exposure period and a 10% exceedance probability (Figure 9), the maximum PGA (73 gal) is seen in Level 2, when using seismic rates calculated with the geological-kinematic parameters, under the time dependent assumption (a Brownian Time Passage model is used, where the conditional probability of occurrence is based on the time elapsed since the last characteristic event, see Part I and Pace et al., 2016 for details). We find in general that the purely geological approach results in higher hazard compared to the ones obtained by the historical-macroseismic earthquake data (historical approach). For a 30 year exposure period (Figure 10), the maximum PGA (274 gal) is seen in both Levels 2 and 3, when using the geological-kinematic approach and Poisson model. Again, we observe that the geological-kinematic approach gives higher hazard compared to the historical approach (in this case, over 2 times higher), and that hazard is also higher when the occurrence rates on the faults have been derived using the Poisson model compared to the time-dependent model. Within the Timpe fault system, for both

Raffaele Azzaro 17/7/17 17:40

Eliminato: of Piedimonte Etneo, Fiumefreddo di Sicilia, Mascali, Giarre, Riposto, Sant'Alfio, Milo, Zafferana, Santa Venerina, Acireale, Aci Catana, Aci Sant'Antonio, Viagrande and Trecastragni

Robin Gee 20/7/17 11:05

Eliminato: here ...he role of site-specific ... [16]

Robin Gee 20/7/17 11:21

Eliminato: ; w... mapped in the format re... [17]

Robin Gee 5/7/17 17:23

Eliminato: In this section, we present the... [18]

Robin Gee 5/7/17 17:34

Eliminato: and computational implementations previously described. Seismic hazard maps are referred to rock conditions (Figures 9-11), and exploratory site-specific results are also given (Figure 12). ... [19]

Raffaele Azzaro 17/7/17 17:44

Eliminato: the ...eological-kinematic ... [20]

Robin Gee 5/7/17 17:39

Eliminato: with ...here the conditional pr... [21]

Raffaele Azzaro 17/7/17 17:43

Eliminato: -kinematic

Robin Gee 5/7/17 17:41

Eliminato: gives higher results...results in ... [22]

Raffaele Azzaro 17/7/17 17:45

Eliminato: Fault ...ault System ... [23]

exposure periods, the Fiandaca fault (FF) dominates the hazard for the historical approach, while for the [geological-kinematic](#) approach the Santa Tecla and Venerina [faults](#) (STF, SVF) dominate the hazard. To give context to these values, the current national hazard map (MPS04, see <http://esse1-gis.mi.ingv.it/>), which considers regional events not modelled in this analysis, shows [PGA values](#) around 0.20 - 0.25 g for the region of Mt Etna, for an exposure period of 50 years. These values fall between the historical and [geological-kinematic](#) approaches of our analysis [considering an exposure period of 30 years](#). [We performed a preliminary disaggregation test in terms of magnitude and distance considering only the area sources of Level 1 \(time independent model\) and the 4 area sources from the MPS04 national hazard model closest to Mt Etna: the results confirm that the hazard at Mt Etna is dominated by the local volcano-tectonic events, and not by the larger \(M6+\) events in the region for return times \$\geq 10^4\$ centuries.](#)

[We also use a logic tree in order to combine the results of the different models.](#) [The purpose of a logic tree is to account for epistemic uncertainty, such as the 3 branching levels used here representing different modelling approaches,](#) meanwhile avoiding duplication of similar models. For this reason, we choose to neglect [Levels 1 and 2](#) in our [logic tree](#) weighting, under the assumption that the same information is contained in Level 3, i.e. the 3D gridded seismicity is a more complex representation of the distributed seismicity in Level 1, and the fault sources are modelled in the same way as in Level 2. For the final logic tree, we therefore weigh the four models in Level 3 ([historical-Poisson, historical-time dependant, geological-Poisson, geological-time dependant](#)) [equally with weights of 0.25.](#) [In the final mean hazard maps, we obtain maximum PGA values of 46 and 176 gal, for exposure periods of 5 and 30 years, respectively. For a 5 year exposure period \(Figure 9, "L3 Tree" frame\), the hazard is highest around the Pernicana \[fault \\(PF\\)\]\(#\), while for a 30 year exposure period \(Figure 10, "L3 Tree" frame\), the hazard is similarly high also around the Santa Tecla and Venerina \[faults \\(STF, SVF\\)\]\(#\).](#)

In some [of the hazard maps, the hazard pattern appears](#) concentrated around the middle of the fault sources [in a radial pattern](#). This is most notable around the Pernicana [fault \(PF\)](#) using the [geological-kinematic](#) approach for an exposure period of 30 years. [This is due to the combination of the following: 1\) The fault sources have been assigned Gaussian \[FMDs\]\(#\) centered near the magnitude of the characteristic earthquake \(i.e. full fault rupture\), and therefore finite ruptures, which have areas defined by the Etna MSR \(see Part I\), float minimally along \[strike\]\(#\) and 2\) The ETNAhy GMPE is in terms of a point source distance metric \(\$R_{hypo}\$ \), which means that ground motion is calculated as a function of distance from the center of the rupture \(we assume hypocenters are located at the center of the ruptures\). The combination of minimal rupture floating and the use of \$R_{hypo}\$ in the GMPE results in a hazard pattern that is highest around the centroid of the fault surface, which is consistent with the assumption that faults rupture bilaterally.](#)

The simplest model, Level 1, is also computed for some spectral ordinates (Figure 11) in addition to PGA values (reported in Figures 9 and 10). For the spectral ordinates considered, SA(0.2s) gives the highest hazard, with maximum values of 109 gal and 241 gal, for 10% exceedance probability on exposure periods of 5 and 30 years, respectively. For all the exposure periods and spectral ordinates calculated, the hazard of Level 1 is dominated by the Pernicana area source, but note the relative increase of values in the south-easternmost area of the Timpe, as the spectral ordinate shifts toward lower frequencies. The results using CRISIS confirm these values, and will be used for the site-specific test, given below.

Robin Gee 5/7/17 20:19
Eliminato: geological
 Raffaele Azzaro 17/7/17 17:45
Eliminato: Faults ...aults (STF, SVF) don... [24]
 Robin Gee 5/7/17 20:19
Eliminato: geological
 Raffaele Azzaro 17/7/17 17:46
Eliminato: given

Robin Gee 5/7/17 17:58
Eliminato: - [25]

Robin Gee 13/7/17 19:56
Formattato [26]

Robin Gee 5/7/17 18:01
Eliminato: ... Combining the models into... [27]

Raffaele Azzaro 17/7/17 17:47
Eliminato: Fault ...ault source...PF), whi... [28]

Robin Gee 5/7/17 21:41
Eliminato: models...f the hazard maps, th... [29]

Raffaele Azzaro 17/7/17 17:48
Eliminato: Fault

Robin Gee 5/7/17 20:20
Eliminato: geological

Laura Peruzza 19/7/17 17:40
Eliminato: MFD

Robin Gee 13/7/17 19:36
Eliminato: I

Raffaele Azzaro 17/7/17 17:49
Eliminato: the fault surface

Robin Gee 5/7/17 22:23
Eliminato: This pattern can be explained when fault geometry is small compared to rupture extent (ruptures do not float very much along the fault surface), coupled with using a GMPE derived in terms of a point source distance metric, such as TL16 which uses R_{hypo} . In this case, hazard is calculated with respect to the center of the rupture, and this point moves very little as we float the ruptures along the fault surface, which causes the observed pattern. -

Lastly, the amplification factors obtained by instrumental measures in the eastern flank of Etna have been used in CRISIS. They give the first seismic hazard site-specific map based on real response data, and clearly illustrate how amplification due to local site conditions can increase the expected ground motion at rock reference sites. Even if these results are preliminary, they can be considered the first example of a new generation of site-specific seismic hazard maps suitable for defining priorities of retrofitting at a local scale. In Figure 12, site-amplified results at two spectral accelerations (0.2 and 1.0s) for a 10% probability of exceedance in 5 and 30 years are given. The obtained values show that the site-specific conditions are by far the most important elements in driving the hazard, and the variability in ground motion introduced alters the spatial correlations of nearby localities. Further studies will deepen these analyses, by checking how we can bridge the gap existing between the probabilistic physically-based models (like the study presented here), and the ones obtained by means of the observed intensities (Azzaro et al., 2008; 2016a). By now, we acknowledge that the two approaches differ mainly in the less inhabited areas where seismic sources are defined by instrumental methods only, thus bouncing back the problem of seismic sources definition essentially to completeness and epistemic uncertainty' issues.

7 Conclusive remarks

This work presents the first seismic hazard maps specific for a volcano, Mt Etna in Sicily, and the implementations introduced ad hoc in two PSHA software packages (CRISIS, Ordaz et al., 2013, and OpenQuake-engine, Pagani et al., 2014). Results are given in terms of acceleration (PGA and spectral ordinates at 0.2, 0.4, and 1.0s) for shorter return periods than those normally used in regulation, i.e. for a 10% exceedance probability in 5 and 30 years (corresponding to return periods of 47-284 years, respectively) as they are intended to be a tool for prioritization of risk mitigation actions.

The main novelties introduced in this study are:

- The derivation and the introduction of a new GMPE into the software, which accounts for the peculiar propagation properties in this volcanic area: it takes into account hypocentral distance (R_{hypo}) and is used jointly with an original magnitude-rupture relationship (see Part I companion paper, Azzaro et al., 2017), derived from the volcanic dataset;
- The implementation of new computational capabilities in PSHA software by introducing the rough volcano topography, which both software benefitted from. Accounting for more realistic source-to-site distances can impact results up to 50% of the expected values for the shallowest sources in the near field;
- The conceptual composition of seismic sources, handled in a framework of increasing complexity. Mt Etna sources are depicted through an extensive analysis of geological, historical and instrumental earthquake data, described in detail in Part I. A basic observation is that a high-quality instrumental monitoring obtained during a 10 year interseismic period at Mt Etna is representative of the frequency-magnitude distribution derived from a long historical catalogue. This encouraged us to use the non-declustered catalogue for parameterizing the seismic sources, potentially opening the usage of generalized, non-Poissonian models for treating the earthquake generation

Laura Peruzza 19/7/17 17:07

Eliminato: if these results

Raffaele Azzaro 17/7/17 17:50

Eliminato: e

Robin Gee 13/7/17 17:53

Eliminato: software

Robin Gee 13/7/17 17:53

Eliminato: development teams

Robin Gee 13/7/17 17:54

Eliminato: this

Robin Gee 13/7/17 17:55

Eliminato: the

Robin Gee 13/7/17 17:55

Eliminato: parameterization

processes in volcanic areas. Further studies are planned to check the [applicability](#) of such assumptions in other contexts.

- The seismic sources have been structured in three independent layers, some of them branching to account for different parameterization (e.g. based on historical or geological constraints, to handle the uncertainty of M_{max} for a fault source), or different assumptions (e.g. about time-dependency, using Poissonian stationary rates, or probability rates [conditioned](#) to the time elapsed since the last major event, based on simplified Brownian Passage Time distributions). We believe in this way the epistemic uncertainties [are](#) properly accounted for.

The [hazard maps computed in our study](#) [have](#) higher spatial resolution than [the national hazard maps](#), [and](#) those referred to rock [conditions](#) (where $V_{s30}=800$ m/s, i.e. soil type A) [indicate](#) significantly higher [hazard](#) than the ones used by regulation, even [though](#) they [only consider](#) surficial volcano-tectonic sources and do not account for the regional sources capable of releasing $M>6$ earthquakes [like the national hazard maps do](#). A preliminary [modelling](#) of site-specific hazard is [also attempted on the flank](#) of Mt Etna, where extensive field [work has](#) been performed for characterizing local amplification factors. [They](#) provide a new picture of expected ground motion, about twice the values assigned to reference [rock sites](#), and [are](#) spatially [uncorrelated](#).

We hope that these analyses [will](#) be deepened and broadened by the extensive microzonation investigations carried out in the frame of [the activities promoted and funded by the Italian Department for Civil Protection](#) (e.g. [http://www.protezionecivile.gov.it/jcms/it/piano_nazionale_art_11.wp](#)), and integrated into the regulation framework, for having realistic and useful ground motion prediction maps devoted to urban planners and structural designers.

Finally, we hope [that](#) components of this work can be useful in the seismic hazard assessment of other volcanic regions.

Acknowledgements

Many thanks are due to [G. Weatherill and an anonymous reviewer](#) for fruitful discussions and suggestions about methodological issues. This study has benefited from funding provided by the Italian Presidenza del Consiglio dei Ministri - Dipartimento della Protezione Civile (DPC), [in the frame of the 2012-14 Agreement with Istituto Nazionale di Geofisica e Vulcanologia-INGV, Projects V3 “Multi-disciplinary analysis of the relationships between tectonic structures and volcanic activity” and S2 “Constraining observations into seismic hazard”](#). This paper does not necessarily represent DPC official opinion and policies.

References

[Abe K.: Magnitudes of major volcanic earthquakes of Japan 1901 to 1925, J. Fac. Sci., Hokkaido Univ. Ser. VII 6, 201-212, 1979.](#)

Robin Gee 13/7/17 17:59

Eliminato: obtained

Robin Gee 13/7/17 18:00

Eliminato: a

Robin Gee 13/7/17 18:01

Eliminato: are

Robin Gee 13/7/17 18:04

Eliminato: maps

Laura Peruzza 12/7/17 16:31

Eliminato: PC activities

Raffaele Azzaro 17/7/17 18:01

Eliminato: of the Projects V3-2012 and V3-2014,

Laura Peruzza 19/7/17 16:53

Eliminato: .

Laura Peruzza 19/7/17 16:53

Eliminato: .

~~Akkar S., Bommer J.J.: Empirical equations for the prediction of PGA, PGV and spectral accelerations in Europe, the Mediterranean region and the Middle East. Seismol Res Lett 81:195–206, 2010.~~

~~Akkar S., Çagnan Z., Yenier E., Erdoğan Ö., Sandikkaya A., Gülkan P.: The recently compiled Turkish strong motion database: preliminary investigation for seismological parameters. J Seismol 14:457–479, 2010.~~

5 | Alparone S., Maiolino V., Mostaccio A., Scaltrito A., Ursino A., Barberi G., D'Amico S., Di Grazia G., Giampiccolo E., Musumeci C., Scarfi L. and Zuccarello L.: Instrumental seismic catalogue of Mt. Etna earthquakes (Sicily, Italy): ten years (2000-2010) of instrumental recordings, Annals of Geophysics, 58, S0435, doi: 10.4401/ag-6591, 2015.

Laura Peruzza 12/7/17 16:33

Eliminato: ...S., Maiolino V., Mostacci (... [30])

Azzaro R.: Seismicity and active tectonics in the Etna region: constraints for a seismotectonic model, In: Mt. Etna: volcano laboratory, A. Bonaccorso, S. Calvari, M. Coltelli, C. Del Negro and S. Falsaperla (eds.), American Geophysical Union, Geophysical monograph, 143, 205-220. 2004.

Laura Peruzza 12/7/17 16:33

Eliminato: ,

10 | [Azzaro R., Barbano M.S., Moroni A., Mucciarelli M. and Stucchi, M.: The seismic history of Catania, Journal of Seismology, 3, 235-252, 1999.](#)

Azzaro R., Barbano MS., D'Amico S., Tuvè T., Albarello D., D'Amico V.: First studies of probabilistic seismic hazard assessment in the volcanic region of Mt. Etna (southern Italy) by means of macroseismic intensities, Bollettino di Geofisica Teorica e Applicata 49 (1), 77-91, 2008.

Laura Peruzza 12/7/17 16:34

Eliminato: MS ...arbano MS., S ...'Amic (... [31])

Azzaro R., Carocci C.F., Maugeri M., Torrisi A.: Microzonazione sismica del versante orientale dell'Etna studi di primo livello. Ed. Le nove Muse, Catania, pp. 181, 2010.

20 | Azzaro R., D'Amico S., Peruzza L. and Tuvè T.: Earthquakes and faults at Mt. Etna (Southern Italy): problems and perspectives for a time-dependent probabilistic seismic hazard assessment in a volcanic region, Boll. Geofis. Teor. App., 53, 75-88, 2012.

Laura Peruzza 12/7/17 16:35

Eliminato: ...R., D'Amico,...S., Peruzz (... [32])

Azzaro R., D'Amico S., Peruzza L. and Tuvè T.: Probabilistic seismic hazard at Mt. Etna (Italy): the contribution of local fault activity in mid-term assessment, J. Volcanol. Geoth. Res., 251, 158-169, 2013.

Laura Peruzza 12/7/17 16:35

Eliminato: ...R., D'Amico,...S., Peruzz (... [33])

25 | Azzaro R., D'Amico S., Tuvè T.: Seismic hazard assessment in the volcanic region of Mt. Etna (Italy): a probabilistic approach based on macroseismic data applied to volcano-tectonic seismicity, Bulletin of Earthquake Engineering 14 (7), 1813-1825, 2016a.

Laura Peruzza 12/7/17 16:35

Eliminato: S ...'Amico S., T (... [34])

Azzaro R., De Rosa R.: Project V3. Multi-disciplinary analysis of the relationships between tectonic structures and volcanic activity (Etna, Vulcano-Lipari system). Final Report November 1st, 2014 - June 30th, 2015, Agreement INGV-DPC 2012-2021, Volcanological programme 2012-2015: Miscellanea INGV, v. 29, 172 pp., 2016b.

Laura Peruzza 12/7/17 16:35

Eliminato: ...R., and ...e Rosa, (... [35])

30 | Azzaro R., Barberi G., D'Amico S., Pace B., Peruzza L., and T. Tuvè: When probabilistic seismic hazard climbs volcanoes: the Mt. Etna case, Italy. Part I: model components for sources parametrization. Submitted to NHES, Special Issue, 2017.

Laura Peruzza 12/7/17 16:35

Eliminato: ...R., Barberi,...G., D'Amico (... [36])

Barani S., Spallarossa D.: Soil amplification in probabilistic ground motion hazard analysis. Bull Earthquake Eng, 1-21, doi:10.1007/s10518-016-9971-y, 2016.

Laura Peruzza 12/7/17 16:35

Eliminato: ...S., & (... [37])

Bindi D., Pacor F., Luzi L., Puglia R., Massa M., Ameri G., Paolucci R.: Ground motion prediction equations derived from the Italian strong motion database. Bull Earthq Eng 9:1899–1920. doi:10.1007/s10518-011-9313-z, 2011.

Boore D.M.: Prediction of ground motion using the stochastic method. Pure Appl. Geophys. 160, 635–676, 2003.

Boore D.M., Atkinson G.M.: Ground-motion prediction equations for the average horizontal component of PGA, PGV, and 5 %-damped PSA at spectral periods between 0.01 s and 100 s. Earthquake Spectra 24:99–13, 2008.

Branca S., Coltelli M., Groppelli G.: Geological evolution of a complex basaltic stratovolcano: Mount Etna, Italy. Ital. J. Geosci., 130 (3), 306-317, DOI: 10.3301/IJG.2011.13, 2011.

Branca S., Ferrara V.: The morphostructural setting of Mount Etna sedimentary basement (Italy): implications for the geometry and volume of the volcano edifice and its flank instability. Tectonophysics, doi: 10.1016/j.tecto.2012.11.011, 2013.

D'Amico S., Meroni F., Sousa M.L., Zonno G.: Building vulnerability and seismic risk analysis in the urban area of Mt. Etna volcano (Italy) Bulletin of Earthquake Engineering 14 (7), 2031-2045, 2016.

De Gori P., Chiarabba C.: Qp structure of Mount Etna: Constraints for the physics of the plumbing system. J. geophys. Res., 110, B05303, doi:10.1029/2003JB002875, 2005.

Giampiccolo E., D'Amico S., Patanè D., S. Gresta: Attenuation and Source Parameters of Shallow Microearthquakes at Mt Etna Volcano, Italy. Bull. Seism. Soc. Am., 184–197, doi: 10.1785/0120050252, 2007.

15 Herak M.: ModelHVSR-A Matlab® tool to model horizontal-to-vertical spectral ratio of ambient noise, Computers Geosciences, 34, 1514-1526, 2008.

[Konno K., Ohmachi T.: Ground-motion characteristics estimated from spectral ratio between horizontal and vertical components of microtremor. Bull. Seism. Soc. Am., 88 \(1\), 228–241, 1998.](#)

Langer H., Tusa G., Scarfi L., R. Azzaro: Ground-motion scenarios on Mt. Etna inferred from empirical relations and synthetic simulations Bulletin of Earthquake Engineering, July 2016, Volume 14, Issue 7, pp 1917–1943, 2016.

20 [Lermo J., Chavez-Garcia FJ.: Site effect evaluation using spectral ratios with only one station. Bull Seism Soc Am 83\(5\): 1574-1594, 1993.](#)

[Lombardo G., Langer H., Gresta S., Rigano R., Monaco C., De Guidi G.: On the importance of geolithological features for the estimate of the site response: the case of Catania metropolitan area \(Italy\). Natural Hazards, 38, 339-354, ISSN: 0921-030X, doi: 10.1007/s11069-005-0386-3, 2006.](#)

25 [Imperatori W., P.M. Mai: The role of topography and lateral velocity heterogeneities on near-source scattering and ground-motion variability. Geophys J Int, 202 \(3\): 2163-2181. doi: 10.1093/gji/ggv281, 2015.](#)

[Nakamura Y.: A method for dynamic characteristics estimation of sub surface using microtremor on the surface. Railw Tech Res Inst Rep 30: 25-33, 1989.](#)

30 [Nogoshi M., Igarashi T.: On the amplitude characteristic of microtremor \(part 2\) \(in Japanese with English abstract\). J Seism Soc Japan 24: 26-40, 1971.](#)

Ordaz M., Martinelli F., D'Amico V. and Meletti C.: CRISIS2008: A flexible tool to perform probabilistic seismic hazard assessment. Seismological Research Letters 84, 495-504, 2013.

Laura Peruzza 12/7/17 16:36

Eliminato: .

Laura Peruzza 12/7/17 16:36

Eliminato: .

Laura Peruzza 12/7/17 16:37

Eliminato: F

Laura Peruzza 12/7/17 16:37

Eliminato: ML

Laura Peruzza 12/7/17 16:37

Eliminato: G

Laura Peruzza 12/7/17 16:36

Eliminato: .

Laura Peruzza 12/7/17 16:37

Eliminato: Stefano

Laura Peruzza 12/7/17 16:38

Eliminato: G.

Laura Peruzza 12/7/17 16:38

Eliminato: L.

Pace B., Visini F. and Peruzza L.: FiSH: MATLAB tools to turn fault data into seismic hazard models, *Seism. Res. Lett.*, 87, 2a, doi: 10.1785/0220150189, 2016.

Panzerà F., Lombardo G., Monaco C., Di Stefano A.: Seismic site effects observed on sediments and basaltic lavas outcropping in a test site of Catania, Italy. *Natural Hazards*, doi: 10.1007/s11069-015-1822-7, 2015.

5 Panzerà F., Lombardo G., Longo E., Langer H., Branca S., Azzaro R., Cicala V., Trimarchi F.: Exploratory seismic site response surveys in a complex geologic area: a case study from Mt. Etna volcano (southern Italy). *Natural Hazards*, vol. 86, p. 385-399, ISSN: 0921-030X, doi: 10.1007/s11069-016-2517-4, 2017.

Panzerà F., Lombardo G., Muzzetta I.: Evaluation of the buildings fundamental period through in-situ experimental techniques in the urban area of Catania, Italy. *Physics And Chemistry of the Earth*. 63, 136-146, ISSN: 1474-7065, doi: DOI 10.1016/j.pce.2013.04.008, 2013.

10 Panzerà F., Sicali S., Lombardo G., Imposa S., Gresta S., D'Amico S.: A microtremor survey to define the subsoil structure in a mud volcanoes area: the case study of Salinelle (Mt Etna, Italy). *Environmental Earth Sciences*, 75, 1140, ISSN: 1866-6280, doi: 10.1007/s12665-016-5974-x, 2016.

Panzerà F., Rigano R., Lombardo G., Cara F., Di Giulio G., Rovelli A.: The role of alternating outcrops of sediments and basaltic lavas on seismic urban scenario: the study case of Catania, Italy. *Bulletin of Earthquake Engineering* 9 (2), 411-439, 2011.

15 Panzerà F., Monelli D., Weatherill G., Danciu L., Crowley H., Silva V., Henshaw P., Butler L., Nastasi M., Panzeri L., Simionato M. and Viganò D.: OpenQuake-engine: An open hazard (and risk) software for the Global Earthquake Model, *Seismol. Res. Lett.*, 85, 692-702; doi:10.1785/0220130087, 2014.

20 Patanè D., Ferrucci F., S. Gresta: Spectral features of microearthquakes in volcanic areas: attenuation in the crust and amplitude response of the site at Mt Etna, Italy, *Bull. Seism. Soc. Am.* 84, 1842-1860, 1994.

Peruzza L., Gee R., Pace B., Roberts G., Scotti O., Visini F., Benedetti L., Pagani M.: PSHA after a strong earthquake: hints for the recovery, *Annals of Geophysics* 59, pp?, 2016

Priolo E.: 2-D spectral element simulation of destructive ground shaking in Catania (Italy). *J. Seismol.*, 3, 289-309, 1999.

25 Rahpeyma S., Halldorsson B., Oliveira CS., Green RA., Jónsson S.: Detailed site effect estimation in the presence of strong velocity reversals within a small-aperture strong-motion array in Iceland. *Soil Dynamics and Earthquake Engineering*. 89, 136-151, doi: 10.1016/j.soildyn.2016.07.001, 2016.

SESAME: Guidelines for the implementation of the H/V spectral ratio technique on ambient vibrations: Measurements, processing and interpretation. SESAME European Research Project WP12, deliverable D23.12, at <http://sesame-fp5.obs.ujfgrenoble.fr/Deliverables>, 2004.

30 Tusa G., Langer H.: Prediction of ground-motion parameters for the volcanic area of Mount Etna. *J Seismol.* doi:10.1007/s10950-015-9508-x, 2016.

Laura Peruzza 12/7/17 16:40
Eliminato: ...B., Visini,...F. and Peruzza ... [38]

Laura Peruzza 12/7/17 16:41
Eliminato: ...M., Monelli,...D., Weather ... [39]

Laura Peruzza 12/7/17 16:41
Eliminato: ...D., F. ... [40]

Laura Peruzza 12/7/17 16:42
Eliminato: R ...ee R., B ...ace B., G ...o ... [41]

Schnabel P. B., Lysmer J. and Seed H. B.: Shake a computer program for earthquake response analysis of horizontally layered sites. Report No. EERC 72 - 12, Earthquake Engineering Research Center, University of California, Berkeley, California, 1972.

Sicali S., Barbano M.S., D'Amico S. and Azzaro R.: Characterization of seismicity at Mt. Etna volcano (Italy) by inter-event time distribution, J. Volcanol. Geotherm. Res., 270, 1-9, 2014.

Stucchi M., Meletti C., Montaldo V., Crowley H., Calvi G.M. and E. Boschi: Seismic Hazard Assessment (2003- 2009) for the Italian Building Code, B. Seismol. Soc. Am., 101, 1885-1911; doi:10.1785/0120100130, 2011.

Yokoyama I.: The largest magnitudes of earthquakes associated with some historical volcanic eruptions and their volcanological significance, Annals of Geophysics 44, 1021-1029, 2001.

Zobin V.M.: Seismic hazard of volcanic activity, J. Volcanol. Geotherm. Res. 112, 1-14, 2001.

Zobin V.M.: Introduction to Volcanic Seismology. Elsevier, 2nd edition, 482 pp., 2012, ISBN: 978-0-444-56375-0.

- Laura Peruzza 12/7/17 16:43
- Eliminato: ,
- Laura Peruzza 12/7/17 16:43
- Eliminato: C.
- Laura Peruzza 12/7/17 16:43
- Eliminato: V.
- Laura Peruzza 12/7/17 16:43
- Eliminato: H.
- Laura Peruzza 12/7/17 16:43
- Eliminato: G.M.
- Raffaele Azzaro 17/7/17 18:17
- Formattato: Apice




Figure 1: **Source** typologies at Mt Etna. a) polygonal area sources representing uniform seismicity: the ones defined in this study (in pale blue and yellow) follow the non-creeping sections of the best-known fault systems; in orange the single area source used in the maps of Italian regulation (ZS9, Stucchi et al., 2011); b) fault sources modelling the main volcano-tectonic structures detected on Etna's flanks (see Table 1 for the nomenclature): the red boxes and lines represent the projection at the surface of the fault planes; c) 3D mesh of point sources, used to model the scattered background seismicity, b-values represented by colors. Details are given in the companion Part I paper (Azzaro et al., 2017).

Raffaele Azzaro 17/7/17 18:10
 Eliminato: source
 Laura Peruzza 12/7/17 13:55
 Eliminato: plane, in black creeping sections




Figure 2: Schematic chart describing the three branching levels of the source model, and depiction of the different source typologies used for modelling. The major seismicity of Level 2 and 3 is modelled using fault sources, where seismicity rates are derived using historical and geological approaches, and both approaches consider both time independence and time dependence.




Figure 3: Predicted mean attenuation-curves for a $M_1=4$ earthquake by the empirical law estimated in this study: ETNAhy, (continuous blue lines), TL16 (continuous red lines), and ITA10 (continuous green line). The dashed lines represent the standard deviation of the mean. The black circles refer to the observations of our dataset with $3.9 \leq M_1 \leq 4.1$; the three frames represent the different soil type according to the EC8 Building code.

5




Figure 4: A topographic profile of Mt Etna shown to scale, extending from the western side of the volcano to the eastern coast (Ionian Sea). Using a hypothetical fault, it can be demonstrated how the source-to-site distance increases ($R_{hypo2} > R_{hypo1}$) if the site is defined on the topographic surface (red triangle) compared to the sea level (clear triangle).

10






Figure 5: **Snapshots** of topography and sources in CRISIS: a) DEM at Mt Etna; b) preliminary fault sources in 3d (note the vertices above the sea level, marked by black dotted line in the cross sections).




Figure 6: **A hypothetical example showing the sensitivity of the hazard results to topography considering area sources and using the OpenQuake-engine.** The source geometries are from this study. Here, all sources are all assigned the same FMD and a depth of 2.5 km, a) Etna DEM, b) hazard without DEM (sites at sea level), c) hazard with DEM (sites on topographic surface), and d) the difference (b-c).

- Raffaele Azzaro 17/7/17 18:11
Eliminato: snapshots
- Robin Gee 10/7/17 10:44
Eliminato: hypothetical
- Robin Gee 10/7/17 11:03
Eliminato: using
- Robin Gee 10/7/17 11:04
Eliminato: e
- Laura Peruzza 12/7/17 13:55
Eliminato: engine
- Robin Gee 10/7/17 10:54
Eliminato: The same area sources are used
- Laura Peruzza 12/7/17 13:55
Eliminato: used
- Robin Gee 10/7/17 11:05
Eliminato: as in
- Robin Gee 10/7/17 12:10
Eliminato: , except here
- Robin Gee 10/7/17 10:57
Eliminato: they are
- Laura Peruzza 19/7/17 17:39
Eliminato: MFD
- Robin Gee 10/7/17 11:01
Eliminato: .
- Robin Gee 10/7/17 11:02
Eliminato: When the sites are defined on a realistic topographic surface, the hazard decreases due to an increase in source-to-site distance.




Figure 7: **Site-specific** response along Mt Etna South-eastern flank (in the inset map): a) sites investigated by HVSR/HVNR measurements and simulated spectral classes; b) spectral shapes defined by grouping the HVNR curves into four classes based on the frequency of the dominant peak: mean site amplification function by red curve, standard deviation by dashed black curves.

Laura Peruzza 12/7/17 13:55
Eliminato: -
 Raffaele Azzaro 17/7/17 18:11
Eliminato: site
 Raffaele Azzaro 17/7/17 18:11
Eliminato: classes




Figure 8: **Simplified** site-specific response along Mt Etna South-eastern flank: a) amplification factors at SA(0.2), obtained by interpolating the measured sites using the Nearest Neighbour algorithm; b) amplification factors as implemented in CRISIS; orange stripe represents the area where amplification factors will be entered in hazard computations.

Raffaele Azzaro 17/7/17 18:12
Eliminato: simplified
 Laura Peruzza 12/7/17 13:55
Eliminato: -




Figure 9: Results for a 10% exceedance probability in 5 years in terms of PGA, when $V_{s30} = 800$ m/s. Thickest lines indicate fault trace




Figure 10: Hazard results for a 10% exceedance probability in 30 years in terms of PGA, when $V_{30} = 800$ m/s. Thickest lines indicate fault traces.





Figure 11: Hazard results of Level 1 at different spectral ordinates for a 10% exceedance probability in 5 and 30 years, and $V_{s30} = 800$ m/s.



5 Figure 12: Site-specific hazard results of Level 1 (CRISIS): in the upper frames, the maps of SA(0.2s) at 10% exceedance probability in 5 (left) and 30 years (right) are obtained for $V_{s30} = 800$ m/s for the whole area; the amplification factors are applied on a stripe on Mt Etna South-eastern flank (dashed black rectangle, see details in Figures 7, 8); the lower frames refer to SA(1.0s).

Period (s)	a	b ₁	b ₂	c ₁	c ₂	h	c ₃	e _B	e _D	R ²	σ _{eve}	σ _{sta}	σ _T	RMSE
0.1	0.859	0.053	0.079	-2.226	0.007	1.424	0.007	0.414	0.421	0.825	0.290	0.232	0.441	0.442
CI95	-1.803	-1.371	-0.118	-2.533	-0.184	0.445	0.003	0.283	0.248					
	3.521	1.476	0.276	-1.919	0.197	3.293	0.011	0.544	0.594					
<i>BS_{mean}</i>	<i>0.849</i>	<i>0.051</i>	<i>0.080</i>	<i>-2.220</i>	<i>0.004</i>	<i>1.231</i>	<i>0.007</i>	<i>0.417</i>	<i>0.425</i>					
<i>BS_s</i>	<i>1.141</i>	<i>0.609</i>	<i>0.087</i>	<i>0.155</i>	<i>0.089</i>	<i>2.865</i>	<i>0.002</i>	<i>0.089</i>	<i>0.100</i>					
0.2	1.062	0.042	0.080	-2.268	0.019	2.697	0.007	0.472	0.567	0.858	0.245	0.224	0.395	0.396
CI95	-1.343	-1.234	-0.096	-2.604	-0.156	1.130	0.003	0.354	0.409					
	3.466	1.318	0.257	-1.933	0.195	4.263	0.011	0.590	0.724					
<i>BS_{mean}</i>	<i>1.073</i>	<i>0.039</i>	<i>0.082</i>	<i>-2.285</i>	<i>0.014</i>	<i>2.596</i>	<i>0.007</i>	<i>0.472</i>	<i>0.568</i>					
<i>BS_s</i>	<i>1.016</i>	<i>0.537</i>	<i>0.076</i>	<i>0.165</i>	<i>0.082</i>	<i>0.943</i>	<i>0.002</i>	<i>0.068</i>	<i>0.075</i>					
0.25	0.993	0.032	0.090	-2.232	0.007	3.172	0.007	0.471	0.518	0.866	0.225	0.222	0.376	0.378
CI95	-1.311	-1.187	-0.078	-2.578	-0.163	1.579	0.003	0.358	0.366					
	3.297	1.250	0.259	-1.886	0.176	4.765	0.011	0.584	0.669					
<i>BS_{mean}</i>	<i>0.999</i>	<i>0.029</i>	<i>0.091</i>	<i>-2.232</i>	<i>0.006</i>	<i>3.080</i>	<i>0.007</i>	<i>0.470</i>	<i>0.515</i>					
<i>BS_s</i>	<i>1.035</i>	<i>0.551</i>	<i>0.077</i>	<i>0.176</i>	<i>0.079</i>	<i>0.910</i>	<i>0.002</i>	<i>0.064</i>	<i>0.075</i>					
0.4	-1.803	1.427	-0.105	-1.941	0.050	3.061	0.005	0.491	0.546	0.883	0.163	0.220	0.334	0.335
CI95	-3.847	0.347	-0.255	-2.243	-0.100	1.466	0.001	0.391	0.412					
	0.240	2.508	0.044	-1.639	0.200	4.655	0.008	0.591	0.680					
<i>BS_{mean}</i>	<i>-1.832</i>	<i>1.446</i>	<i>-0.108</i>	<i>-1.946</i>	<i>0.049</i>	<i>3.038</i>	<i>0.005</i>	<i>0.491</i>	<i>0.546</i>					
<i>BS_s</i>	<i>0.928</i>	<i>0.505</i>	<i>0.072</i>	<i>0.146</i>	<i>0.074</i>	<i>0.558</i>	<i>0.002</i>	<i>0.063</i>	<i>0.068</i>					
0.5	-1.491	1.239	-0.081	-1.929	0.123	3.392	0.005	0.485	0.509	0.878	0.148	0.236	0.339	0.340
CI95	-3.574	0.143	-0.232	-2.252	-0.030	1.709	0.001	0.383	0.373					
	0.592	2.336	0.071	-1.607	0.277	5.075	0.008	0.587	0.646					
<i>BS_{mean}</i>	<i>-1.508</i>	<i>1.248</i>	<i>-0.081</i>	<i>-1.935</i>	<i>0.120</i>	<i>3.367</i>	<i>0.005</i>	<i>0.487</i>	<i>0.512</i>					
<i>BS_s</i>	<i>0.999</i>	<i>0.529</i>	<i>0.074</i>	<i>0.157</i>	<i>0.072</i>	<i>0.620</i>	<i>0.002</i>	<i>0.065</i>	<i>0.069</i>					
1	-0.628	0.308	0.064	-1.533	0.239	2.732	0.001	0.465	0.406	0.869	0.125	0.265	0.354	0.355
CI95	-2.794	-0.835	-0.095	-1.837	0.082	0.722	-0.003	0.359	0.265					
	1.538	1.452	0.222	-1.229	0.397	4.742	0.004	0.571	0.547					
<i>BS_{mean}</i>	<i>-0.613</i>	<i>0.298</i>	<i>0.066</i>	<i>-1.540</i>	<i>0.233</i>	<i>2.674</i>	<i>0.001</i>	<i>0.463</i>	<i>0.405</i>					
<i>BS_s</i>	<i>1.098</i>	<i>0.586</i>	<i>0.082</i>	<i>0.155</i>	<i>0.077</i>	<i>0.886</i>	<i>0.002</i>	<i>0.069</i>	<i>0.073</i>					
1.25	-1.856	0.789	0.017	-1.487	0.188	3.052	-0.001	0.431	0.367	0.878	0.132	0.248	0.341	0.343
CI95	-3.952	-0.315	-0.135	-1.798	0.035	0.989	-0.004	0.329	0.230					
	0.241	1.893	0.170	-1.177	0.341	5.116	0.003	0.534	0.504					

<i>BS_{mean}</i>	-1.805	0.771	0.020	-1.501	0.190	3.058	-0.001	0.432	0.368						
<i>BS_σ</i>	0.983	0.512	0.072	0.170	0.075	1.001	0.002	0.066	0.072						
2	-4.859	1.750	-0.061	-1.200	0.077	2.847	-0.004	0.368	0.349	0.870	0.156	0.252	0.355	0.357	
CI95	-7.033	0.601	-0.220	-1.516	-0.082	0.248	-0.008	0.262	0.207						
	-2.684	2.900	0.098	-0.884	0.235	5.446	-0.001	0.475	0.491						
<i>BS_{mean}</i>	-4.781	1.722	-0.057	-1.219	0.079	2.821	-0.004	0.369	0.349						
<i>BS_σ</i>	1.070	0.580	0.082	0.182	0.082	1.368	0.002	0.068	0.073						
2.5	-5.108	1.663	-0.042	-1.100	0.058	2.615	-0.005	0.336	0.333	0.862	0.158	0.256	0.359	0.360	
CI95	-7.299	0.503	-0.203	-1.408	-0.101	0.189	-0.009	0.228	0.190						
	-2.918	2.823	0.119	-0.791	0.218	5.420	-0.002	0.443	0.476						
<i>BS_{mean}</i>	-4.998	1.623	-0.036	-1.135	0.058	2.675	-0.005	0.334	0.330						
<i>BS_σ</i>	1.122	0.596	0.082	0.201	0.084	1.603	0.002	0.066	0.072						
5	-3.239	0.339	0.115	-1.109	0.186	0.955	-0.003	0.290	0.221	0.840	0.165	0.265	0.364	0.365	
CI95	-5.438	-0.836	-0.048	-1.348	0.030	-2.690	-0.006	0.182	0.079						
	-1.041	1.514	0.278	-0.869	0.342	4.600	0.001	0.397	0.364						
<i>BS_{mean}</i>	-3.115	0.255	0.127	-1.086	0.189	0.420	-0.003	0.293	0.225						
<i>BS_σ</i>	1.138	0.622	0.086	0.148	0.091	1.212	0.002	0.062	0.066						
10	-4.009	0.512	0.087	-1.342	0.140	1.892	-0.001	0.357	0.320	0.862	0.166	0.245	0.352	0.353	
CI95	-6.146	-0.626	-0.071	-1.608	-0.013	0.356	-0.004	0.253	0.181						
	-1.871	1.649	0.244	-1.077	0.294	4.140	0.002	0.462	0.459						
<i>BS_{mean}</i>	-3.965	0.480	0.093	-1.346	0.134	1.509	-0.001	0.357	0.318						
<i>BS_σ</i>	1.045	0.561	0.078	0.148	0.081	1.365	0.002	0.064	0.069						

Table ESM1: Regression coefficients for PSA (cm/s2) at the different periods. R^2 is the determination coefficient. CI95 indicates the confidence intervals at 95% confidence level. BS_{mean} and BS_{σ} are the mean value and the standard deviation of each coefficient, respectively, estimated by applying the bootstrap technique.




Figure ESM1: Comparison of the attenuation curves ITA10 (Bindi et al. 2011) and TL16 (Tusa and Langer, 2016) with the ones from this study for PSA considering $M_L=4$ and several periods T .